
AMERICAN INTERNATIONAL INDUSTRIES



MATERIAL SAFETY DATA SHEET

Section 1. Product and Company Identification

Product Name: Gigi Sure Clean DATE: 7/1/2013

Formula: 30-0625 REV. 03

Item#: 0755 (826454), 0750, 0760, 0760CN, 87-5597, 87-5599, 87-

Manufacturer: American International Industries

2220 Gaspar Ave

Los Angeles, CA 90040

Chem-Tel: (800) 255-3924

Section 2. Hazardous Identification

Flammability: Highly Flammable



Potential Health Effects, Signs and Symptoms of Exposure:

Primary Route of Entry: Eyes, skin or inhalation

Eye: Eye Contact with the product may produce transient superficial irritation. Some redness and/or

stinging may occur.

Skin: Skin Contact with the product may cause irritation or drying of the skin.

Ingestion: Possible mild gastrointestinal irritation with nausea, vomiting and diarrhea.

Inhalation: May cause central nervous system depression.

Section 3. Composition / Information on Ingredients

NOT FOR USE ON SKIN. PRODUCT IS A SURFACE CLEANER

Hazardous Composition:


	Component	CAS#	용	Exposure Limits ppm	
_				ACGIH-TLV	OSHA-PEL
	Isopropyl Alcohol	67-63-0	60 - 65%	200ppm	400ppm
	Solvent Naphtha	64742-89-8	35 - 40%	400ppm	400ppm

Section 4. First Aid Measures

First Aid for Eye: Immediately flush with water for 15 minutes, including under eyelids. Seek medical attention if

discomfort persists.





MATERIAL SAFETY DATA SHEET

First Aid for Skin: Wash off affected areas with plenty of soap and water. If discomfort or irritation persists contact

a physician.

First Aid for Inhalation: Remove to fresh air. Seek medical attention if discomfort persists.

First Aid for Ingestion: Rinse mouth out with water. Only induce vomiting if directed by a physician. Never give

anything by mouth to an unconscious person. Seek prompt medical attention.

Section 5. Fire Fighting Measures

Flash Point (°F/°C): 52°F (11.11°C) (Tag Closed Cup)

Flammable Limit LEL: 1.0 (vol%): UEL: 12.5

Auto-ignition Temp.

(vol%)

Not available

Extinguisher Media: Alcohol Foam, CO2, Dry Chemical, Water Fog

Procedures: breathing apparatus and full protective clothing.

Unusual Fire and

Fire Fighting

Explosion Hazards:

containers.

Section 6. Accidental Release Measures

Spill or Release Procedures:

For small spills (e.g., < 1 gallon) wear appropriate personal equipment (e.g., goggles, gloves). Maximize ventilation (open doors and windows) and secure sources of ignition. Remove spilled material and place to appropriate closed container(s) for disposal. Dispose of properly in accordance with local, state, and federal regulations. Wash all affected areas and outside of container with plenty of warm water and soap. Remove any contaminated clothing and wash thoroughly before reuse.


Fire should be fought from a safe distance. Firefighters should wear full face, self-contained

Closed containers exposed to excessive heat may rupture. Do not crush or puncture

For spills > 1 gallon, deny entry to all unprotected individuals. Contain spill with inert material (e.g., sand or earth). Transfer product to containers for recovery or proper disposal. Remove contaminated clothing promptly and wash affected areas with soap and water. Keep spills and cleaning runoffs out of municipal sewers and open bodies of water.

Section 7. Handling and Storage

AMERICAN INTERNATIONAL INDUSTRIES



MATERIAL SAFETY DATA SHEET

Handling & Storing:

Keep container closed when not in use. Store in cool place. Keep away from heat, sparks and flame. Do not lay the container on its side. Use with proper ventilation. Avoid prolonged breathing vapor. Avoid contact with eyes and prolonged or repeated skin contact. Static electricity may accumulate and cause a fire hazard.

Information about the empty container:

Do not re-use the container. Container will be hazardous when emptied. Residues will be flammable. Keep away from heat, sparks and flame. Do not puncture or cut the container and do not weld on or near the container.

Section 8. Exposure Controls / Personal Protective Equipment

Respiratory Protections (Specific Type):

None required, when used with adequate ventilation.

Ventilation to be Used:

Use adequate ventilation.

Other Protective Clothing and Equipment:

None required under normal conditions of use. When handling large quantities (e.g., > 1 gallon), wear protective eyeglasses, gloves, boot, and apron per OSHA regulations (29 CFR 1910.133).

Hygienic Work Practices:

Wash hand thoroughly after using this product and before eating, drinking, or smoking.

Section 9. Physical and Chemical Properties

Slightly soluble

Appearance @ 25°C: Clear liquid Viscosity (RVT): Not applicable

Odor @ 25°C:Solvent odorVapor Pressure:Not available.pHNot applicableVapor Density:Heavier Than AirSpecific Gravity:~0.77Evaporation Rate:Slower Than Ether

Ignition: Not applicable Material V.O.C.: 6.44 lb/gl
Melting Point: Not applicable
Boiling Range: 180 - 369°F

Section 10. Stability and Reactivity

Stability: Stable


Solubility in Water

Hazardous Decomposition Products:

Irritating vapors and toxic gases when involved in fire.

Incompatibility (Materials to Avoid):

Strong oxidizing agents.



MATERIAL SAFETY DATA SHEET

Hazardous Polymerization:

Will not occur

Conditions to Avoid: Use or storage near open flames, sparks, high heat (>100°F), or other sources.

Section 11. Toxicological Information

Skin Irritation: Not available

Eye Irritation: Not available

Sensitization: Not available

Acute Toxicity

Not available

(LC50):

Acute Toxicity

(LC50):

Not available

Subacute Toxicity: Not available

Chronic Toxicity: Not available

Section 12. Ecological Information

Biodegradation: Not available.

Bioaccumulation: Not available.

Aquatic Toxicology: Not available.

Other Information: Not available.


Section 13. Disposable Considerations

Do not dispose of the emptied container unless the contents have been completely removed and container has been flushed with a clean neutral solvent and then dried up. Do not dispose the emptied container unlawfully. Observe all federal, state, and local laws.

Section 14. Transportation Information

<DOT Information>

AMERICAN INTERNATIONAL INDUSTRIES



MATERIAL SAFETY DATA SHEET

Proper Shipping Name (49CFR 172.101): Flammable Liquid n.o.s. (Isopropyl Alcohol, Solvent Naphtha)

Hazard Class: 3

UN/NA: UN1993

Packing Group:

Section 15. Regulatory Information

Regulatory information available upon request.

Section 16. Other Information

No additional information available.