SAFETY DATA SHEET



1. Identification

Product identifier MATRIX COLOR SYNC PERMANENT HAIR COLOURS - GROUP 10

Other means of identification

SDS number 00-21-0000254

Recommended use Personal care product used for cosmetic effect.

Recommended restrictions None known.

Manufacturer/Importer/Supplier/Distributor information

US Address: L'Oreal USA Products, Inc

133 Terminal Avenue Clark, NJ 07066

USA

Canadian Address: L'Oreal Canada

4895 rue Hickmore

Ville St-Laurent, H4T 1K5

Canada

Emergency Phone #: 1-800-535-5053 (International: 352-323-3500)

In Canada - 1-613-996-6666 (Canutec (*666 Cellular))

For further Information: 1-732-499-2741

Poison Control #: 412-390-3326

2. Hazard(s) identification

Physical hazards Not classified.

Health hazards Skin corrosion/irritation Category 2

Serious eye damage/eye irritation Category 1

Specific target organ toxicity, single exposure Category 3 respiratory tract irritation

OSHA defined hazards Not classified.

Label elements



Signal word Danger

Hazard statement Causes skin irritation. Causes serious eye damage. May cause respiratory irritation.

Precautionary statement

Prevention Wash thoroughly after handling. Use only outdoors or in a well-ventilated area. Wear eye

protection/face protection. Wear protective gloves.

Response If on skin: Wash with plenty of water. If inhaled: Remove person to fresh air and keep comfortable

for breathing. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a poison center/doctor. If skin irritation occurs: Get medical advice/attention. Take off contaminated clothing and wash it before

reuse.

Storage Store in a well-ventilated place. Keep container tightly closed. Store locked up.

Material name: MATRIX COLOR SYNC PERMANENT HAIR COLOURS - GROUP 10 91007 MX Version #: 01 Issue date: 09-20-2019

Disposal

Dispose of contents/container in accordance with local/regional/national/international regulations.

Hazard(s) not otherwise classified (HNOC)

None known.

Supplemental information

None.

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
DECETH-3		66455-15-0	9
LAURETH-12		68439-50-9	7
ETHANOLAMINE		141-43-5	5.12
LAURIC ACID		143-07-7	3
SILICA DIMETHYL SILYLA	TE	68611-44-9	1.2

^{*}Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

4. First-aid measures

Inhalation Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a poison

center or doctor/physician if you feel unwell.

Remove contaminated clothing. Wash with plenty of soap and water. If skin irritation occurs: Get Skin contact

medical advice/attention. Wash contaminated clothing before reuse.

Eye contact Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if

present and easy to do. Continue rinsing. Get medical attention immediately.

Ingestion Rinse mouth. Get medical attention if symptoms occur.

Most important

symptoms/effects, acute and

delayed

Indication of immediate

medical attention and special treatment needed

Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Permanent eye damage including blindness could result. May cause respiratory irritation.

Skin irritation. May cause redness and pain.

Provide general supportive measures and treat symptomatically. Keep victim under observation.

Symptoms may be delayed.

If you feel unwell, seek medical advice (show the label where possible). Ensure that medical **General information** personnel are aware of the material(s) involved, and take precautions to protect themselves.

5. Fire-fighting measures

Suitable extinguishing media

Unsuitable extinguishing

media

Alcohol resistant foam. Powder. Carbon dioxide (CO2).

Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from

the chemical

During fire, gases hazardous to health may be formed.

Special protective equipment

and precautions for firefighters

Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

Fire fighting

equipment/instructions

Move containers from fire area if you can do so without risk.

Specific methods Use standard firefighting procedures and consider the hazards of other involved materials.

General fire hazards No unusual fire or explosion hazards noted.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Avoid breathing mist/vapors. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Material name: MATRIX COLOR SYNC PERMANENT HAIR COLOURS - GROUP 10 91007 MX Version #: 01 Issue date: 09-20-2019

Methods and materials for containment and cleaning up

Use water spray to reduce vapors or divert vapor cloud drift.

Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS.

Environmental precautions

Avoid discharge into drains, water courses or onto the ground.

7. Handling and storage

Precautions for safe handling

Do not get in eyes, on skin, or on clothing. Avoid breathing mist/vapors. Avoid prolonged exposure. Provide adequate ventilation. Wear appropriate personal protective equipment. Observe good industrial hygiene practices.

Value

Conditions for safe storage, including any incompatibilities

Store locked up. Store in tightly closed container. Keep out of the reach of children. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection

Occupational exposure limits

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit. At this time, the other constituents have no known exposure limits.

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)
At this time, the other constituents have no known exposure limits.

Components	Туре	Value	
ETHANOLAMINE (CAS 141-43-5)	PEL	6 mg/m3	
		3 ppm	
US. OSHA Table Z-3 (29 CFR 19	10.1000)		
Components	Туре	Value	
SILICA DIMETHYL SILYLATE (CAS 68611-44-9)	TWA	0.8 mg/m3	
		20 mppcf	
US. ACGIH Threshold Limit Valu	ies		
Components	Туре	Value	
ETHANOLAMINE (CAS 141-43-5)	STEL	6 ppm	
	TWA	3 ppm	
US. NIOSH: Pocket Guide to Che	emical Hazards		
Components	Туре	Value	
ETHANOLAMINE (CAS 141-43-5)	STEL	15 mg/m3	
		6 ppm	
	TWA	8 mg/m3	
		3 ppm	

Biological limit values

No biological exposure limits noted for the ingredient(s).

Appropriate engineering

controls

Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Provide eyewash station and safety shower.

Individual protection measures, such as personal protective equipment

Eye/face protection Applicable for industrial settings only. Chemical respirator with organic vapor cartridge and full

facepiece.

Skin protection

Hand protection Applicable for industrial settings only. Wear appropriate chemical resistant gloves.

Other Applicable for industrial settings only. Wear appropriate chemical resistant clothing.

Applicable for industrial settings only. Chemical respirator with organic vapor cartridge and full Respiratory protection

facepiece.

Thermal hazards Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective

equipment to remove contaminants.

9. Physical and chemical properties

Appearance

Physical state Liquid. Shaded Color Odor Characteristic. Not available. Odor threshold

Ηq 10

Melting point/freezing point Not available.

Initial boiling point and boiling

range

> 212 °F (> 100 °C)

Flash point > 212.0 °F (> 100.0 °C) Closed Cup

Evaporation rate Not available. Not applicable. Flammability (solid, gas) Upper/lower flammability or explosive limits

Flammability limit - lower

(%)

Flammability limit - upper

Not available.

Not available.

(%)

Not available. Explosive limit - lower (%) Not available. Explosive limit - upper (%) Vapor pressure Not available. Vapor density Not available. Not available. Relative density

Solubility(ies)

Not available. Solubility (water) Not available. Partition coefficient

(n-octanol/water)

Auto-ignition temperature Not available. **Decomposition temperature** Not available. Not available. **Viscosity**

Other information

Not explosive. **Explosive properties** Oxidizing properties Not oxidizing.

10. Stability and reactivity

The product is stable and non-reactive under normal conditions of use, storage and transport. Reactivity

Material is stable under normal conditions. **Chemical stability**

Possibility of hazardous

reactions

No dangerous reaction known under conditions of normal use.

Conditions to avoid Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. Contact with

incompatible materials.

Incompatible materials Strong acids. Strong oxidizing agents.

Hazardous decomposition

products

No hazardous decomposition products are known.

Material name: MATRIX COLOR SYNC PERMANENT HAIR COLOURS - GROUP 10

11. Toxicological information

Information on likely routes of exposure

Inhalation May cause irritation to the respiratory system. Prolonged inhalation may be harmful.

Skin contact Causes skin irritation.

Prolonged or repeated exposure may cause liver and kidney damage. These effects have not

been observed in humans.

Eye contact Causes serious eye damage.

Ingestion Expected to be a low ingestion hazard.

Symptoms related to the physical, chemical and toxicological characteristics

Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Permanent eye damage including blindness could result. May cause respiratory irritation.

Skin irritation. May cause redness and pain.

Information on toxicological effects

Acute toxicity Not known.

Product Species Test Results

MATRIX COLOR SYNC PERMANENT HAIR COLOURS - GROUP 10

<u>Acute</u>

Dermal

ATEmix 48260 mg/kg

Oral

ATEmix 28860 mg/kg

Components Species Test Results

DECETH-3 (CAS 66455-15-0)

Acute Dermal

LD50 Rat > 2000 mg/kg Based on test data for

structurally similar materials.

Oral

LD50 Rat > 2000 mg/kg Based on test data for

structurally similar materials.

ETHANOLAMINE (CAS 141-43-5)

<u>Acute</u>

Dermal

LD50 Rabbit 2504 mg/kg OECD 402

Inhalation

Vapor

LC50 Rat > 1.3 mg/l, 6 h

Oral

LD50 Rat 1515 mg/kg OECD 401

LAURETH-12 (CAS 68439-50-9)

Acute

Dermal

LD50 Rat > 2000 mg/kg OECD 402

Inhalation

Aerosol

LC50 Rat > 1.6 mg/l, 4 h OECD 403

Oral

LD50 Rat > 2000 mg/kg OECD 401

LAURIC ACID (CAS 143-07-7)

Acute

Dermal

LD50 Rabbit > 2000 mg/kg OECD 434

Components **Species Test Results** Inhalation Vapor LC50 Rat > 0.1621 mg/l, 4 h Oral LD50 Rat > 5000 mg/kg OECD 401 Skin corrosion/irritation Causes skin irritation. **Irritation Corrosion - Skin OECD 404 ETHANOLAMINE** Result: Corrosive Species: Rabbit LAURETH-12 **OECD 404** Result: Not Irritating Species: Rabbit LAURIC ACID **OECD 404** Result: Slightly Irritating Species: Rabbit OECD 404, Based on test data for structurally similar DECETH-3 materials. Result: Slightly Irritating Species: Rabbit Serious eye damage/eye Causes serious eye damage. irritation **Irritation Corrosion - Eye ETHANOLAMINE OECD 405** Result: Corrosive Species: Rabbit LAURETH-12 **OECD 405** Result: Corrosive Species: Rabbit **OECD 405** LAURIC ACID Result: Corrosive Species: Rabbit DECETH-3 Result: Corrosive Species: Rabbit Respiratory or skin sensitization Respiratory sensitization Due to partial or complete lack of data the classification is not possible.

Skin sensitization Due to partial or complete lack of data the classification is not possible.

Skin sensitization

LAURETH-12 **OECD 406**

> Result: Not Sensitizing Species: Guinea pig

LAURIC ACID **OECD 406**

> Result: Not Sensitizing Species: Guinea pig

OECD 406, Based on test data for structurally similar **DECETH-3**

materials.

Result: Not Sensitizing Species: Guinea pig Result: Not Sensitizing Species: Guinea pig

Germ cell mutagenicity Due to partial or complete lack of data the classification is not possible.

Mutagenicity

ETHANOLAMINE

LAURETH-12 Result: In vitro and in vivo tests did not show mutagenic

ETHANOLAMINE Result: In vitro and in vivo tests did show mutagenic effects DECETH-3 Result: In vitro tests did not show mutagenic effects LAURIC ACID Result: In vitro tests did not show mutagenic effects

Not classifiable as to carcinogenicity to humans. Due to partial or complete lack of data the Carcinogenicity

classification is not possible.

IARC Monographs. Overall Evaluation of Carcinogenicity

Not listed.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1052)

Not regulated.

US. National Toxicology Program (NTP) Report on Carcinogens

Not listed.

Reproductive toxicityDue to partial or complete lack of data the classification is not possible.

Developmental effects

LAURETH-12 >= 250 mg/kg bw/d OECD 416

Result: NOAEL Species: Rat

ETHANOLAMINE >= 450 mg/kg bw/d OECD 414

Result: NOAEL Species: Rat

LAURIC ACID 1000 mg/kg bw/d OECD 422

Result: NOAEL

Species: Rabbit

Reproductivity

LAURETH-12 >= 250 mg/kg bw/d OECD 416

Result: NOAEL Species: Rat

LAURIC ACID 1000 mg/kg bw/d OECD 422

Result: NOAEL

ETHANOLAMINE 300 mg/kg bw/d OECD 416

Result: NOAEL Species: Rat

Specific target organ toxicity -

single exposure

May cause respiratory irritation.

Specific target organ toxicity -

repeated exposure

Due to partial or complete lack of data the classification is not possible.

>= 500 mg/kg bw/d OECD 408

Result: NOAEL Species: Rat

Test Duration: 90 d

DECETH-3 100 mg/kg bw/d OECD 407, Based on test data for structurally

similar materials. Result: NOAEL Species: Rat Test Duration: 28 d

LAURIC ACID 1000 mg/kg bw/d OECD 422

Result: NOAEL

Species: Rat

ETHANOLAMINE 150 mg/m3 air OECD 412, Inhalation

Result: NOAEC Species: Rat Test Duration: 28 d

300 mg/kg bw/d OECD 416, Oral

Result: NOAEL Species: Rat

Aspiration hazard Due to partial or complete lack of data the classification is not possible.

Chronic effects May be harmful if absorbed through skin.

Prolonged or repeated exposure may cause liver and kidney damage. These effects have not

been observed in humans.

Further information The reference to any animal testing for individual constituents mentioned in this document is

based on public, third-party data.

12. Ecological information

Ecotoxicity The product is not classified as environmentally hazardous. However, this does not exclude the

possibility that large or frequent spills can have a harmful or damaging effect on the environment.

Components		Species	Test Results
DECETH-3 (CAS 664	55-15-0)		
Aquatic			
Acute	F050	Daniel daniel and an instance	4.0
Algae	EC50	Desmodesmus subspicatus	1.8 mg/l, 72 h 92/69/EWG
Crustacea	EC50	Daphnia magna	0.39 mg/l, 48 h 92/69/EWG
Fish	LC50	Cyprinus carpio	1.2 mg/l, 96 h EU C.1
Other	EC0	Activated sludge of a predominantly domestic sewage	140 mg/l, 3 h 88/302/EG
Chronic			
Crustacea	NOEC	Daphnia magna	<= 1 mg/l, 21 d
Fish	NOEC	Lepomis macrochirus	0.16 mg/l, 10 d
ETHANOLAMINE (CA	S 141-43-5)		
Aquatic			
<i>Acute</i> Algae	EC50	Pseudokirchneriella subcapitata	2.8 mg/l, 72 h OECD 201
Crustacea	EC50	Daphnia magna	65 mg/l, 48 h EU C.2
-	LC50	•	349 mg/l, 96 h EU C.1
Fish		Cyprinus carpio	•
Other	EC10	Activated sludge of a predominantly domestic sewage	> 1000 mg/l, 30 min OECD 209
Chronic			
Crustacea	NOEC	Daphnia magna	0.85 mg/l, 21 d OECD 211
Fish	NOEC	Oryzias latipes	1.24 mg/l, 41 d OECD 210
_AURETH-12 (CAS 68	8439-50-9)		
Aquatic			
<i>Acute</i> Algae	EC50	Pseudokirchneriella subcapitata	0.29 mg/l, 72 h OECD 201
Crustacea	EC50	Daphnia magna	0.53 mg/l, 48 h
Fish	LC50	Danio rerio	1.2 mg/l, 96 h EU C.1
			_
Other	EC50	Pseudomonas putida	> 10000 mg/l, 16.9 h DIN 38412, 8
<i>Chronic</i> Crustacea	NOEC	Daphnia magna	0.77 mg/l, 21 d
_AURIC ACID (CAS 1		Dapinia magna	5 1g,,, 2.1 G
Aquatic	40-07-7)		
Acute			
Algae	EC50	Pseudokirchneriella subcapitata	> 7.6 mg/l, 72 h OECD 201
Crustacea	EC50	Daphnia magna	3.6 mg/l, 48 h OECD 202
Fish	LC50	Oryzias latipes	5 mg/l, 96 h OECD 203
Other	EC10	Pseudomonas putida	> 1000 mg/l, 30 min OECD 209
istence and degrada	bility		
Biodegradability	•		
Percent degrada	tion (Aerobic biod	-	
DECETH-3		78 % OECD 301 B	

Per

ETHANOLAMINE

LAURETH-12

Result: Readily Biodegradable

Test Duration: 28 d > 90 % OECD 301 A

Result: Readily Biodegradable Test Duration: 21 d

95 % OECD 301 F Result: Readily Biodegradable Test Duration: 28 d

Bioaccumulative potential

Partition coefficient n-octanol / water (log Kow)

ETHANOLAMINE -2.3 OECD 107 LAURETH-12 6.1 OECD 117 4.2

LAURIC ACID **Bioaccumulation**

ETHANOLAMINE Result: Bioaccumulation is unlikely.

Mobility in soil No data available.

Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation

potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Dispose of **Disposal instructions**

contents/container in accordance with local/regional/national/international regulations.

Dispose in accordance with all applicable regulations. Local disposal regulations

Waste from residues / unused

products

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see:

Disposal instructions).

Since emptied containers may retain product residue, follow label warnings even after container is Contaminated packaging

emptied. Empty containers should be taken to an approved waste handling site for recycling or

disposal.

14. Transport information

DOT

FINISHED GOODS

Not regulated as dangerous goods.

BULK

Not regulated as dangerous goods.

IATA

FINISHED GOODS

Not regulated as dangerous goods.

Not regulated as dangerous goods.

IMDG

FINISHED GOODS

Not regulated as dangerous goods.

BULK

Not regulated as dangerous goods.

15. Regulatory information

US federal regulations This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication

Standard, 29 CFR 1910.1200.

Toxic Substances Control Act (TSCA)

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

Not listed.

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1052)

Superfund Amendments and Reauthorization Act of 1986 (SARA)

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous

No (Exempt)

chemical

SARA 313 (TRI reporting)

Not regulated.

Material name: MATRIX COLOR SYNC PERMANENT HAIR COLOURS - GROUP 10

SDS US 9 / 10 91007 MX Version #: 01 Issue date: 09-20-2019

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act

Not regulated.

(SDWA)

16. Other information, including date of preparation or last revision

09-20-2019 Issue date

Version # 01

NFPA ratings Health: 3

Flammability: 1

Instability: 0

Disclaimer The information provided in this Safety Data Sheet is correct to the best of our knowledge,

information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other

materials or in any process, unless specified in the text.

Material name: MATRIX COLOR SYNC PERMANENT HAIR COLOURS - GROUP 10 91007 MX Version #: 01 Issue date: 09-20-2019