REDKEN

SAFETY DATA SHEET

1. Identification

Product identifier REDKEN PILLOW PROOF BLOW DRY EXPRESS PRIMER

Other means of identification

SDS number 30-31-0000060

Recommended use Personal care product used for cosmetic effect.

Recommended restrictions None known.

Manufacturer/Importer/Supplier/Distributor information

US Address: L'Oreal USA Products, Inc

133 Terminal Avenue Clark. NJ 07066

USA

Canadian Address: L'Oreal Canada

4895 rue Hickmore

Ville St-Laurent, H4T 1K5

Canada

Emergency Phone #: 1-800-535-5053 (International: 352-323-3500)

In Canada - 1-613-996-6666 (Canutec (*666 Cellular))

For further Information: 1-732-499-2741

Poison Control #: 412-390-3326

2. Hazard(s) identification

Physical hazardsFlammable liquidsCategory 3Health hazardsSerious eye damage/eye irritationCategory 1

OSHA defined hazards Not classified.

Label elements





Signal word Danger

Hazard statement Flammable liquid and vapor. Causes serious eye damage.

Precautionary statement

Prevention Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Keep container tightly

closed. Ground/bond container and receiving equipment. Use explosion-proof

electrical/ventilating/lighting equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Wear protective gloves/eye protection/face protection.

Response If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a poison center/doctor. In case of fire: Use

appropriate media to extinguish.

Storage Store in a well-ventilated place. Keep cool.

Disposal Dispose of contents/container in accordance with local/regional/national/international regulations.

Material name: REDKEN PILLOW PROOF BLOW DRY EXPRESS PRIMER 35137 RDK26 Version #: 01 Issue date: 08-12-2020

Hazard(s) not otherwise classified (HNOC)

None known.

Supplemental information

None.

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
TRISILOXANE		107-51-7	10
LACTIC ACID		50-21-5	3.38
GLYCERIN		56-81-5	2.25
ETHANOL		64-17-5	1.25

^{*}Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

4. First-aid measures

Inhalation Move to fresh air. Call a physician if symptoms develop or persist.

Take off immediately all contaminated clothing. Rinse skin with water/shower. Get medical Skin contact

attention if irritation develops and persists.

Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if Eve contact

present and easy to do. Continue rinsing. Get medical attention immediately.

Rinse mouth. Get medical attention if symptoms occur. Ingestion

Most important

symptoms/effects, acute and delaved

Indication of immediate

medical attention and special treatment needed

Provide general supportive measures and treat symptomatically. Thermal burns: Flush with water immediately. While flushing, remove clothes which do not adhere to affected area. Call an ambulance. Continue flushing during transport to hospital. Keep victim under observation.

Severe eve irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred

Symptoms may be delayed.

Take off all contaminated clothing immediately. Ensure that medical personnel are aware of the **General information**

material(s) involved, and take precautions to protect themselves.

vision. Permanent eye damage including blindness could result.

Wash contaminated clothing before reuse.

5. Fire-fighting measures

Suitable extinguishing media

Unsuitable extinguishing

media

Water fog. Foam. Dry chemical powder. Carbon dioxide (CO2).

Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from

the chemical

of ignition and flash back. During fire, gases hazardous to health may be formed.

Special protective equipment

and precautions for firefighters

Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

Vapors may form explosive mixtures with air. Vapors may travel considerable distance to a source

In case of fire and/or explosion do not breathe fumes. Move containers from fire area if you can do

Fire fighting equipment/instructions

so without risk.

Specific methods Use standard firefighting procedures and consider the hazards of other involved materials.

General fire hazards Flammable liquid and vapor.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Wear appropriate protective equipment and clothing during clean-up. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Material name: REDKEN PILLOW PROOF BLOW DRY EXPRESS PRIMER 35137 RDK26 Version #: 01 Issue date: 08-12-2020

Methods and materials for containment and cleaning up

Keep combustibles (wood, paper, oil, etc.) away from spilled material. Take precautionary measures against static discharge. Use only non-sparking tools.

Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal. Following product recovery, flush area with water.

Small Spills: Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal. Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS.

Environmental precautions

Avoid discharge into drains, water courses or onto the ground.

7. Handling and storage

Precautions for safe handling

Do not handle, store or open near an open flame, sources of heat or sources of ignition. Protect material from direct sunlight. When using do not smoke. Explosion-proof general and local exhaust ventilation. Take precautionary measures against static discharges. All equipment used when handling the product must be grounded. Use non-sparking tools and explosion-proof equipment. Do not get this material in contact with eyes. Avoid prolonged exposure. Wear appropriate personal protective equipment. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities

Keep away from heat, sparks and open flame. Store in a cool, dry place out of direct sunlight. Store in tightly closed container. Store in a well-ventilated place. Keep out of the reach of children. Keep in an area equipped with sprinklers. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection

Occupational exposure limits

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit. At this time, the other constituents have no known exposure limits.

IIS OSHA Table	7-1 Limits for	Air Contaminante	(29 CFR 1910.1000)
US. USHA LADIE	: Z- 1 LIIIIII 101	All Collabilitiants	(23 CFK 1310.1000)

Components	Туре	Value	Form
ETHANOL (CAS 64-17-5)	PEL	1900 mg/m3	
		1000 ppm	
GLYCERIN (CAS 56-81-5)	PEL	5 mg/m3	Respirable fraction.
		15 mg/m3	Total dust.
US. ACGIH Threshold Limit Value	S		
Components	Туре	Value	
ETHANOL (CAS 64-17-5)	STEL	1000 ppm	
US. NIOSH: Pocket Guide to Cher	nical Hazards		
Components	Туре	Value	
ETHANOL (CAS 64-17-5)	TWA	1900 mg/m3	
		1000 ppm	

Biological limit values

No biological exposure limits noted for the ingredient(s).

Appropriate engineering controls

Explosion-proof general and local exhaust ventilation. Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Provide eyewash station.

Individual protection measures, such as personal protective equipment

Applicable for industrial settings only. Wear safety glasses with side shields (or goggles) and a Eye/face protection

face shield.

Skin protection

Hand protection Applicable for industrial settings only. Wear appropriate chemical resistant gloves.

Other Applicable for industrial settings only. Wear appropriate chemical resistant clothing. Respiratory protection Applicable for industrial settings only. If engineering controls do not maintain airborne

concentrations below recommended exposure limits (where applicable) or to an acceptable level (in countries where exposure limits have not been established), an approved respirator must be

worn.

Thermal hazards Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

9. Physical and chemical properties

Appearance

Physical state Liquid.
Form Bi-Phase
Color Not available.
Odor Characteristic.
Odor threshold Not available.

pH 2.9 - 3.5 (water phase)

Melting point/freezing point Not available.

Initial boiling point and boiling

range

> 212 °F (> 100 °C)

Flash point > 104.0 °F (> 40.0 °C) Closed Cup

Evaporation rate Not available.

Flammability (solid, gas) Not applicable.

Upper/lower flammability or explosive limits

Flammability limit - lower

(%)

Not available.

Flammability limit - upper

(%)

Not available.

Explosive limit - lower (%) Not available.
Explosive limit - upper (%) Not available.

Vapor pressure Not available.

Vapor density Not available.

Relative density Not available.

Solubility(ies)

Solubility (water) Not available.

Partition coefficient Not available.

(n-octanol/water)

Auto-ignition temperature Not available.

Decomposition temperature Not available.

Viscosity Not available.

Other information

Density 1 - 1.04 g/cm³ (water phase) 0.82 - 0.99 g/cm³ (oil phase)

Explosive properties Not explosive. **Oxidizing properties** Not oxidizing.

10. Stability and reactivity

ReactivityThe product is stable and non-reactive under normal conditions of use, storage and transport.

Chemical stability Material is stable under normal conditions.

Possibility of hazardous

reactions

No dangerous reaction known under conditions of normal use.

Conditions to avoid Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. Avoid

temperatures exceeding the flash point. Contact with incompatible materials.

Incompatible materials Strong oxidizing agents.

Material name: REDKEN PILLOW PROOF BLOW DRY EXPRESS PRIMER

Hazardous decomposition products

No hazardous decomposition products are known.

11. Toxicological information

Information on likely routes of exposure

Inhalation Prolonged inhalation may be harmful.

Skin contact No adverse effects due to skin contact are expected.

Eye contact Causes serious eye damage.

Ingestion Expected to be a low ingestion hazard.

Symptoms related to the physical, chemical and toxicological characteristics Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred

vision. Permanent eye damage including blindness could result.

Information on toxicological effects

Acute toxicity Not known.

Product Test Results Species

REDKEN PILLOW PROOF BLOW DRY EXPRESS PRIMER

Acute

Dermal

ATEmix 12310 mg/kg

Oral

ATEmix 15200 mg/kg

Components **Species Test Results**

ETHANOL (CAS 64-17-5)

Acute

Dermal

> 20000 mg/kg LD50 Rabbit

Inhalation

Vapor

Rat LC50 124.7 mg/l, 4 h OECD 403

Oral

LD50 Rat 10470 mg/kg OECD 401

GLYCERIN (CAS 56-81-5)

Acute

Dermal

LD50 Rabbit > 18700 mg/kg bw

Inhalation

Rat LC50 > 570 mg/L air, 1 h

Oral

LD50 Rat 27200 mg/kg bw

LACTIC ACID (CAS 50-21-5)

Acute

Dermal

LD50 Rabbit > 2000 mg/kg EPA OPP 81-2

Inhalation

Mist

LC50 Rat > 7.94 g/l, 4 h OECD 403

Oral

LD50 Rat 3543 mg/kg EPA OPP 81-1

TRISILOXANE (CAS 107-51-7)

Acute

Dermal

LD50 Rat > 2000 mg/kg bw

Components	Species	Test Results
Inhalation		
LC50	Rat	> 22.6 mg/l, 4 h
Oral		
LD50	Rat	> 2000 mg/kg bw
Skin corrosion/irritation	Due to partial or comp skin contact are expe	plete lack of data the classification is not possible. No adverse effects due to cted.
Irritation Corrosion	- Skin	
TRISILOXANE		OECD 401
		Result: Not Irritating Species: Rabbit
ETHANOL		OECD 404
		Result: Not Irritating Species: Rabbit
LACTIC ACID		OECD 404
		Result: Severely Irritating
GLYCERIN		Species: Rabbit Result: Not Irritating
GLICERIN		Species: Rabbit
Serious eye damage/eye irritation	Causes serious eye o	·
Irritation Corrosion	ı - Fve	
ETHANOL		OECD 405
		Result: Irritating
LACTIC ACID		Species: Rabbit OECD 438
27.01107.012		Result: Severely Irritating
TDIOU OVANIE		Species: ex vivo
TRISILOXANE		OPPTS 870.2400 Result: Not Irritating
		Species: Rabbit
GLYCERIN		Result: Not Irritating
Respiratory or skin sensitiz	ation	Species: Rabbit
Respiratory sensitization		plete lack of data the classification is not possible.
Skin sensitization	·	plete lack of data the classification is not possible.
Skin sensitization	Due to partial of com	prote lask of data are stated measure to het pessible.
GLYCERIN		167 mg/m3 air OECD 413, Inhalation
		Result: NOAEL
		Species: Rat Test Duration: 90 d
LACTIC ACID		EPA OPP 81-6
		Result: Not Sensitizing
ETHANOL		Species: Guinea pig OECD 406
LITANOL		Result: Not Sensitizing
		Species: Guinea pig
TRISILOXANE		OECD 406 Result: Not Sensitizing
		Species: Guinea pig
GLYCERIN		Result: Not Sensitizing
0	Due to montial on com-	Species: Guinea pig
Germ cell mutagenicity	Due to partial or com	plete lack of data the classification is not possible.
Mutagenicity ETHANOL		Result: In vitro and in vivo tests did not show mutagenic
2.1.7.102		effects.
GLYCERIN		Result: In vitro and in vivo tests did not show mutagenic
LACTIC ACID		effects. Result: In vitro tests did not show mutagenic effects
Carcinogenicity	Not classifiable as to	carcinogenicity to humans. Due to partial or complete lack of data the
- an omogomony	classification is not po	

IARC Monographs. Overall Evaluation of Carcinogenicity

Not listed.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1052)

Not regulated.

US. National Toxicology Program (NTP) Report on Carcinogens

Not listed.

Reproductive toxicity Possible reproductive hazard.

Developmental effects

ETHANOL > 20000 ppm OECD 414. No effects on development

> Result: NOAEL Species: Rat

GLYCERIN 1310 mg/kg bw/d, No effects on development

Result: NOAEL Species: Rat

TRISILOXANE 31 mg/l OECD 422, No effects on development

Result: NOAEC Species: Rat

Reproductivity

GLYCERIN 2000 mg/kg bw/d, No effects on fertility

Result: NOAEL Species: Rat

ETHANOL 20700 mg/kg bw/d OECD 416, No effects on fertility

Result: NOAEL Species: Rat

TRISILOXANE 31 mg/l OECD 422, No effects on fertility

Result: NOAEC Species: Rat

Specific target organ toxicity -

single exposure

ETHANOL

Due to partial or complete lack of data the classification is not possible.

Specific target organ toxicity -

repeated exposure

Due to partial or complete lack of data the classification is not possible.

1730 mg/kg bw/d OECD 408, Oral Result: NOAEL Species: Rat

TRISILOXANE 25 - 250 mg/kg bw/d OECD 407

Result: NOAEL Species: Rat Test Duration: 28 d 7.74 mg/l OECD 422 Result: LOAEC Species: Rat

7.74 mg/l OECD 422, Inhalation

Result: NOAEC Species: Rat

GLYCERIN 8000 mg/kg bw/d, Oral

Result: NOAEL Species: Rat Test Duration: 2 yr

Due to partial or complete lack of data the classification is not possible. **Aspiration hazard**

Further information The reference to any animal testing for individual constituents mentioned in this document is

based on public, third-party data.

12. Ecological information

Ecotoxicity The product is not classified as environmentally hazardous. However, this does not exclude the

possibility that large or frequent spills can have a harmful or damaging effect on the environment.

Components		Species	Test Results	
ETHANOL (CAS 64-17-5)				
Aquatic				
Acute				
Algae	EC50	Pseudokirchneriella subcapitata	22200 mg/l, 96 h	
Crustacea	EC50	Ceriodaphnia dubia	5012 mg/l, 48 h	
Fish	LC50	Pimephales promelas	15300 mg/l, 96 h	

Components		Species	Test Results
Other	IC50	Activated sludge of a predominantly domestic sewage	> 1000 mg/l, 3 h
Chronic			
Crustacea	NOEC	Daphnia magna	9.6 mg/l, 9 d
Fish	NOEC	Danio rerio	250 mg/l, 120 h OECD 212
GLYCERIN (CAS 56-8	31-5)		
Aquatic			
Acute			
Algae	EC0	Scenedesmus quadricauda	> 10000 mg/l, 192 h
Crustacea	EC50	Daphnia magna	1955 mg/l, 48 h
Fish	LC50	Oncorhynchus mykiss	54000 mg/l, 96 h
Other	NOEC	Pseudomonas putida	> 10000 mg/l, 16 h
LACTIC ACID (CAS 5	0-21-5)		
Aquatic			
Acute			
Algae	EC50	Pseudokirchneriella subcapitata	3500 mg/l, 72 h OECD 201
Crustacea	EC50	Daphnia magna	130 mg/l, 48 h OECD 202
Fish	LC50	Danio rerio	320 mg/l, 96 h OECD 203
Other	ED50	Activated sludge of a predominantly domestic sewage	> 100 mg/l, 3 h OECD 209
TRISILOXANE (CAS	107-51-7)		
Aquatic			
Algae		Pseudokirchneriella subcapitata	> 9.4 μg/l, 72 h
Crustacea		Daphnia magna	> 20 μg/l, 48 h
Fish		Oncorhynchus mykiss	> 19.4 µg/l, 96 h
nictores and degrade	hilitu.		-

Persistence and degradability

Biodegradability

Percent degradation (Aerobic biodegradation)

ETHANOL 84 %

Result: Readily Biodegradable

Test Duration: 20 d

GLYCERIN OECD 301

Result: Readily Biodegradable

OECD 301 D LACTIC ACID

Result: Readily Biodegradable **TRISILOXANE**

0 % OECD 310

Result: Not Readily Biodegradable

Test Duration: 28 d

Bioaccumulative potential

Partition coefficient n-octanol / water (log Kow)

ETHANOL -0.31 **GLYCERIN** -1.76

LACTIC ACID -0.62 OECD 117

Mobility in soil No data available.

Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation

potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Disposal instructions Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Dispose of

contents/container in accordance with local/regional/national/international regulations.

Local disposal regulations

Dispose in accordance with all applicable regulations. Waste from residues / unused

products

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see:

Disposal instructions).

Contaminated packaging

Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal.

14. Transport information

DOT

FINISHED GOODS

UN number UN1993

UN proper shipping name FLAMMABLE LIQUID, N.O.S. (TRISILOXANE, ISODODECANE), Limited Quantity

Class 3 Packing group III

Transport hazard class(es)

Label(s) Limited Quantity

Packaging exceptions 150 LTD QTY Net Inner Capacity 5.0 L

BULK

UN number UN1993

UN proper shipping name FLAMMABLE LIQUID, N.O.S. (TRISILOXANE, ISODODECANE)

Class 3
Packing group III
Transport hazard class(es)
Label(s) 3

Special provisions B1, B52, IB3, T4, TP1, TP29

Packaging non bulk 203

IATA

FINISHED GOODS

UN number ID8000

UN proper shipping name CONSUMER COMMODITY

Class 9

Packing group Not applicable.

ERG Number 9L

BULK

UN number UN1993

UN proper shipping name FLAMMABLE LIQUID, N.O.S. (TRISILOXANE, ISODODECANE)

Class 3
Packing group III
ERG Number 3L

IMDG

FINISHED GOODS

UN number UN1993

UN proper shipping name FLAMMABLE LIQUID, N.O.S. (TRISILOXANE, ISODODECANE), Limited Quantity

Class 3
Packing group III
Environmental Hazards

Marine pollutant No.

Transport hazard class(es)

Label(s)Limited QuantityEmSF-E, S-ELTD QTY Net Inner Capacity5.0 L

BULK

UN number UN1993

UN proper shipping name FLAMMABLE LIQUID, N.O.S. (TRISILOXANE, ISODODECANE)

Class 3
Packing group III
Environmental hazards

15. Regulatory information

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication **US federal regulations**

Standard, 29 CFR 1910.1200.

Toxic Substances Control Act (TSCA)

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

ETHANOL (CAS 64-17-5) Listed.

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1052)

Not regulated.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous

No (Exempt)

chemical

SARA 313 (TRI reporting)

Not regulated.

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act

Not regulated.

(SDWA)

FEMA Priority Substances Respiratory Health and Safety in the Flavor Manufacturing Workplace

ETHANOL (CAS 64-17-5) Low priority

GLYCERIN (CAS 56-81-5) Other Flavoring Substances with OSHA PEL's

16. Other information, including date of preparation or last revision

08-12-2020 Issue date

Version # 01

NFPA ratings Health: 3

Flammability: 2 Instability: 0

Disclaimer The information provided in this Safety Data Sheet is correct to the best of our knowledge,

information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other

materials or in any process, unless specified in the text.

35137 RDK26 Version #: 01 Issue date: 08-12-2020