SAFETY DATA SHEET



1. Identification

| Product identifier | L'ORÉAL PROFESSIONNEL SERIE EXPERT CURL IDENTITY MOUSSE 10-IN-1 |
|---------------------------------|---|
| Other means of identification | |
| SDS number | 21-91-0000175 |
| Recommended use | Personal care product used for cosmetic effect. |
| Recommended restrictions | None known. |
| Manufacturer/Importer/Supplier | /Distributor information |
| US Address: | L'Oreal USA Products, Inc |
| | 133 Terminal Avenue |
| | Clark, NJ 07066 |
| | USA |
| Canadian Address: | L'Oreal Canada |
| | 4895 rue Hickmore |
| | Ville St-Laurent, H4T 1K5 |
| | Canada |
| Emergency Phone # : | 1-800-535-5053 (International: 352-323-3500) |
| | In Canada - 1-613-996-6666 (Canutec (*666 Cellular)) |
| For further Information: | 1-732-499-2741 |
| Poison Control # : | 412-390-3326 |

2. Hazard(s) identification

| Physical hazards | Flammable aerosols | Category 1 |
|----------------------|----------------------|---------------|
| | Gases under pressure | Liquefied gas |
| Health hazards | Not classified. | |
| OSHA defined hazards | Not classified. | |
| Label elements | | |
| | | |

| Signal word | Danger |
|--|--|
| Hazard statement | Extremely flammable aerosol. Contains gas under pressure; may explode if heated. |
| Precautionary statement | |
| Prevention | Keep away from heat/sparks/open flames/hot surfaces No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. |
| Response | Wash hands after handling. |
| Storage | Protect from sunlight. Store in a well-ventilated place. Do not expose to temperatures exceeding 50°C/122°F. |
| Disposal | Dispose of waste and residues in accordance with local authority requirements. |
| Hazard(s) not otherwise classified (HNOC) | None known. |
| Supplemental information | None. |

3. Composition/information on ingredients

Mixtures

| Chemical name | Common name and synonyms | CAS number | % |
|---------------|--------------------------|------------|------|
| ISOBUTANE | | 75-28-5 | 2.8 |
| BUTANE | | 106-97-8 | 1.2 |
| GLYCERIN | | 56-81-5 | 1.01 |
| PROPANE | | 74-98-6 | 1 |

*Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

4. First-aid measures

| Inhalation | Move to fresh air. Call a physician if symptoms develop or persist. | |
|--|---|--|
| Skin contact | No adverse effects due to skin contact are expected. | |
| Eye contact | No specific first aid measures noted. | |
| Ingestion | Not likely, due to the form of the product. In the unlikely event of swallowing contact a physician or poison control center. | |
| Most important symptoms/effects, acute and delayed | Not available. | |
| Indication of immediate medical attention and special treatment needed | Provide general supportive measures and treat symptomatically. | |
| General information | Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. | |

5. Fire-fighting measures

| Suitable extinguishing media | Water fog. Foam. Dry chemical powder. Carbon dioxide (CO2). |
|--|---|
| Unsuitable extinguishing media | Do not use water jet as an extinguisher, as this will spread the fire. |
| Specific hazards arising from the chemical | Contents under pressure. Pressurized container may explode when exposed to heat or flame. During fire, gases hazardous to health may be formed. |
| Special protective equipment and precautions for firefighters | Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA. |
| Fire fighting equipment/instructions | In case of fire: Stop leak if safe to do so. Do not move cargo or vehicle if cargo has been exposed to heat. Move containers from fire area if you can do so without risk. Containers should be cooled with water to prevent vapor pressure build up. For massive fire in cargo area, use unmanned hose holder or monitor nozzles, if possible. If not, withdraw and let fire burn out. |
| Specific methods | Use standard firefighting procedures and consider the hazards of other involved materials. Move containers from fire area if you can do so without risk. In the event of fire and/or explosion do not breathe fumes. |
| General fire hazards | Extremely flammable aerosol. Contents under pressure. Pressurized container may explode when exposed to heat or flame. |
| 6. Accidental release measures | |

| Personal precautions, protective equipment and emergency procedures | Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Keep out of low areas. Many gases are heavier than air and will spread along ground and collect in low or confined areas (sewers, basements, tanks). Wear appropriate protective equipment and clothing during clean-up. Emergency personnel need self-contained breathing equipment. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS. |
|---|---|
| Methods and materials for containment and cleaning up | Refer to attached safety data sheets and/or instructions for use. Stop leak if you can do so without risk. Move the cylinder to a safe and open area if the leak is irreparable. Isolate area until gas has dispersed. Keep combustibles (wood, paper, oil, etc.) away from spilled material. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water. |
| | Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination. For waste disposal, see section 13 of the SDS. |
| Environmental precautions | Avoid discharge into drains, water courses or onto the ground. |

7. Handling and storage

| Precautions for safe handling | Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. All equipment used when handling the product must be grounded. Close valve after each use and when empty. Protect containers from physical damage; do not drag, roll, slide, or drop. When moving containers, even for short distances, use a cart (trolley, hand truck, etc.) designed to transport containers. Suck back of water into the container must be prevented. Do not allow backfeed into the container. Purge air from system before introducing gas. Use only properly specified equipment which is suitable for this product, its supply pressure and temperature. Contact your gas supplier if in doubt. Do not re-use empty containers. Avoid prolonged exposure. Use only in well-ventilated areas. Wear appropriate personal protective equipment. Observe good industrial hygiene practices. | |
|---|---|--|
| Conditions for safe storage, including any incompatibilities | Level 1 Aerosol. | |
| | Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C/122 °F. Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. This material can accumulate static charge which may cause spark and become an ignition source. Store in tightly closed container. Store in a well-ventilated place. Stored containers should be periodically checked for general condition and leakage. Keep out of the reach of children. Store away from incompatible materials (see Section 10 of the SDS). | |
| 8. Exposure controls/personal protection | | |

Occupational exposure limits

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit. At this time, the other constituents have no known exposure limits.

| US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR | 1910.1000) |
|--|------------|
|--|------------|

| Components | Туре | Value | Form |
|------------------------------------|---|-------------------------------|-----------------------|
| GLYCERIN (CAS 56-81-5) | PEL | 5 mg/m3 | Respirable fraction. |
| | | 15 mg/m3 | Total dust. |
| PROPANE (CAS 74-98-6) | PEL | 1800 mg/m3 | |
| | | 1000 ppm | |
| US. ACGIH Threshold Limit | Values | | |
| Components | Туре | Value | |
| BUTANE (CAS 106-97-8) | STEL | 1000 ppm | |
| ISOBUTANE (CAS 75-28-5) | STEL | 1000 ppm | |
| US. NIOSH: Pocket Guide to | Chemical Hazards | | |
| Components | Туре | Value | |
| BUTANE (CAS 106-97-8) | TWA | 1900 mg/m3 | |
| | | 800 ppm | |
| ISOBUTANE (CAS 75-28-5) | TWA | 1900 mg/m3 | |
| | | 800 ppm | |
| PROPANE (CAS 74-98-6) | TWA | 1800 mg/m3 | |
| | | 1000 ppm | |
| logical limit values | No biological exposure limits noted for | the ingredient(s). | |
| propriate engineering trols | Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. | | |
| vidual protection measures, | such as personal protective equipme | nt | |
| Eye/face protection | Applicable for industrial settings only. | Vear safety glasses with side | shields (or goggles). |
| Skin protection Hand protection | Applicable for industrial settings only. V | Vear appropriate chemical re | sistant gloves. |
| Other | Applicable for industrial settings only. | Near appropriate chemical re- | sistent slathing |

| Respiratory protection | Applicable for industrial settings only. If permissible levels are exceeded use NIOSH mechanical filter / organic vapor cartridge or an air-supplied respirator. |
|-----------------------------------|--|
| Thermal hazards | Wear appropriate thermal protective clothing, when necessary. |
| General hygiene considerations | When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. |

9. Physical and chemical properties

| Appearance | |
|--|---|
| Physical state | Liquid. |
| Form | Aerosol. |
| Color | Not available. |
| Odor | Characteristic. |
| Odor threshold | Not available. |
| рН | 4.9 - 5.4 (liquid) |
| Melting point/freezing point | Not available. |
| Initial boiling point and boiling range | > 212 °F (> 100 °C) (liquid) |
| Flash point | > 212.0 °F (> 100.0 °C) Closed Cup (liquid) |
| Evaporation rate | Not available. |
| Flammability (solid, gas) | Not applicable. |
| Upper/lower flammability or exp | losive limits |
| Flammability limit - lower (%) | Not available. |
| Flammability limit - upper (%) | Not available. |
| Explosive limit - lower (%) | Not available. |
| Explosive limit - upper (%) | Not available. |
| Vapor pressure | Not available. |
| Vapor density | Not available. |
| Relative density | Not available. |
| Solubility(ies) | |
| Solubility (water) | Not available. |
| Partition coefficient (n-octanol/water) | Not available. |
| Auto-ignition temperature | Not available. |
| Decomposition temperature | Not available. |
| Viscosity | Not available. |
| Other information | |
| Explosive properties | Not explosive. |
| Heat of combustion (NFPA 30B) | 5.43 kJ/g |
| Oxidizing properties | Not oxidizing. |
| 10. Stability and reactivity | |
| Reactivity | The product is stable and non-reactive under normal conditions of use, storage and transport. |
| Chemical stability | Material is stable under normal conditions. |
| Possibility of hazardous reactions | No dangerous reaction known under conditions of normal use. |

11. Toxicological information

Information on likely routes of exposure

| Information on likely routes of Inhalation | Prolonged inhalation may be | harmful | |
|--|---|--|--|
| Skin contact | No adverse effects due to ski | | |
| | | - | |
| Eye contact | No adverse effects due to eye contact are expected. | | |
| Ingestion | Expected to be a low ingestion hazard. | | |
| Symptoms related to the physical, chemical and toxicological characteristics | Not available. | | |
| nformation on toxicological ef | fects | | |
| Acute toxicity | Not known. | | |
| Product | Species | Test Results | |
| L'ORÉAL PROFESSIONNEL SEI | RIE EXPERT CURL IDENTITY I | MOUSSE 10-IN-1 | |
| Acute | | | |
| Dermal | | | |
| ATEmix | | 2.632e+006 mg/kg | |
| Oral | | | |
| ATEmix | | 235300 mg/kg | |
| Components | Species | Test Results | |
| BUTANE (CAS 106-97-8) | | | |
| Acute | | | |
| Inhalation | | | |
| Gas | | | |
| LC50 | Mouse | 1237 mg/l, 2 Hours | |
| GLYCERIN (CAS 56-81-5) | | | |
| <u>Acute</u> | | | |
| Dermal | | | |
| LD50 | Rabbit | > 18700 mg/kg bw | |
| Inhalation | | | |
| LC50 | Rat | > 570 mg/L air, 1 h | |
| Oral | | | |
| LD50 | Rat | 27200 mg/kg bw | |
| Skin corrosion/irritation | No adverse effects due to ski | n contact are expected. | |
| Irritation Corrosion - S | kin | | |
| BUTANE GLYCERIN | | Result: Contact with liquid form may cause frostbite. Result: Not Irritating Species: Rabbit | |
| Serious eye damage/eye irritation | No adverse effects due to eye | e contact are expected. | |
| Irritation Corrosion - E | уе | | |
| BUTANE GLYCERIN | | Result: Contact with liquid form may cause frostbite. Result: Not Irritating Species: Rabbit | |
| Respiratory or skin sensitizatio | n | | |
| Respiratory sensitization | Not a respiratory sensitizer. | | |
| Skin sensitization | This product is not expected | to cause skin sensitization. | |
| Skin sensitization | | | |
| GLYCERIN | | 167 mg/m3 air OECD 413, Inhalation Result: NOAEL Species: Rat Test Duration: 90 d Result: Not Sensitizing Species: Guinea pig | |

| Germ cell mutagenicity | No data avail mutagenic or | | oonents present at greater than 0.1% are |
|---|--|--|--|
| Mutagenicity BUTANE | matagonio or | - | d in vivo tests did not show mutagenic |
| GLYCERIN | | effects. | d in vivo tests did not show mutagenic |
| Carcinogenicity | Not classifiab | le as to carcinogenicity to humans. | |
| IARC Monographs. Overall | Evaluation of C | Carcinogenicity | |
| Not listed. OSHA Specifically Regulate | ed Substances | (29 CFR 1910.1001-1052) | |
| Not regulated. | | | |
| US. National Toxicology Pr | ogram (NTP) R | eport on Carcinogens | |
| Not listed. | This was durate | | |
| Reproductive toxicity | i nis product | is not expected to cause reproductiv | e or developmental effects. |
| Developmental effects GLYCERIN BUTANE | | Result: NOAEL Species: Rat 19678 mg/m³ OE Result: NOAEC | No effects on development |
| Reproductivity | | Species: Rat | |
| GLYCERIN | | Result: NOAEL Species: Rat | No effects on fertility |
| BUTANE | | 7131 mg/m³ OEC Result: NOAEC Species: Rat | D 422 |
| Specific target organ toxicity - single exposure | Not classified | l. | |
| Specific target organ toxicity - repeated exposure BUTANE | Not classified | 7214 mg/m³ OEC | م 422 م |
| GLYCERIN | | Result: NOAEC Species: Rat Test Duration: 28 8000 mg/kg bw/d Result: NOAEL Species: Rat Test Duration: 2 y | d Oral |
| Aspiration hazard | Not an aspira | tion hazard. | |
| Further information | The reference to any animal testing for individual constituents mentioned in this document is based on public, third-party data. | | |
| 12. Ecological information | n | | |
| Ecotoxicity | The product is not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment. | | |
| Components | | Species | Test Results |
| GLYCERIN (CAS 56-81-5) Aquatic | | | |
| Acute | | | |
| Algae | EC0 | Scenedesmus quadricauda | > 10000 mg/l, 192 h |
| Crustacea | EC50 | Daphnia magna | 1955 mg/l, 48 h |
| Fish | LC50 | Oncorhynchus mykiss | 54000 mg/l, 96 h |
| Other | NOEC | Pseudomonas putida | > 10000 mg/l, 16 h |

Persistence and degradability

Biodegradability

Percent degradation (Aerobic biodegradation) BUTANE

| GLYCERIN | | Result: Readily Biodegradable Test Duration: 385.5 Hours OECD 301 Result: Readily Biodegradable |
|---------------------------|--------------------------|--|
| Bioaccumulative potential | | |
| Partition coefficient n-o | ctanol / water (log Kow) | |
| BUTANE | | 2.89 |
| GLYCERIN | | -1.76 |
| ISOBUTANE | | 2.76 |
| PROPANE | | 2.36 |
| Mobility in soil | No data available. | |
| Other educates offerste | No other adverse environ | mental offects (e.g. ezene depletion ph |

Other adverse effectsNo other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation
potential, endocrine disruption, global warming potential) are expected from this component.

100 %

13. Disposal considerations

| Disposal instructions | Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Contents under pressure. Do not puncture, incinerate or crush. Dispose of contents/container in accordance with local/regional/national/international regulations. |
|--|---|
| Local disposal regulations | Dispose in accordance with all applicable regulations. |
| Hazardous waste code | This product is ignitable (D001) RCRA hazardous wastes when intended for disposal. |
| Waste from residues / unused products | Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions). |
| Contaminated packaging | Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal. Do not re-use empty containers. |

14. Transport information

DOT

| FINISHED GOODS | |
|----------------------------|---------------------------------------|
| UN number | UN1950 |
| UN proper shipping name | AEROSOLS, FLAMMABLE, Limited Quantity |
| Class | 2.1 |
| Packing group | Not applicable. |
| Transport hazard class(es) | |
| Label(s) | Limited Quantity |
| Packaging exceptions | 306 |
| LTD QTY Net Inner Capacity | 1.0 L |

BULK

Not regulated as dangerous goods.

IATA

| FINISHED GOODS | | |
|-----------------------------------|---------------------------|--|
| UN number | ID8000 | |
| UN proper shipping name | CONSUMER COMMODITY | |
| Class | 9 - Class 9 | |
| Packing group | Not applicable. | |
| Transport hazard class(es) | | |
| Label(s) | Class 9, Limited Quantity | |
| ERG Number | 9L | |
| LTD QTY Net Inner Capacity | 0.5 L | |
| BULK | | |
| Not regulated as dangerous goods. | | |
| IMDG | | |
| FINISHED GOODS | | |

| FINISHED GOODS | |
|-------------------------|---------------------------------------|
| UN number | UN1950 |
| UN proper shipping name | AEROSOLS, FLAMMABLE, Limited Quantity |
| Class | 2.1 |
| | |

| Packing group | Not applicable. | |
|---|---|---|
| Environmental Hazards | No. | |
| Marine pollutant Transport hazard class(es) | NO. | |
| Label(s) | Limited Quantity | |
| EmS | F-D, S-U | |
| LTD QTY Net Inner Capacity BULK | 1.0 L | |
| Not regulated as dangerous g | pods. | |
| General information | Avoid transport on vehicles where the load space is not separated from the driver's compartment. Ensure vehicle driver is aware of the potential hazards of the load and knows what to do in the event of an accident or an emergency. Before transporting product containers: Ensure that containers are firmly secured. Ensure cylinder valve is closed and not leaking. Ensure valve outlet cap nut or plug (where provided) is correctly fitted. Ensure valve protection device (where provided) is correctly fitted. Ensure adequate ventilation. Ensure compliance with applicable regulations. | |
| 15. Regulatory information | 1 | |
| US federal regulations | This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200. | |
| Toxic Substances Control A | ct (TSCA) | |
| TSCA Section 12(b) Exp Not regulated. | ort Notification (40 CFR 707, Subpt. D) | |
| CERCLA Hazardous Substa | nce List (40 CFR 302.4) | |
| BUTANE (CAS 106-97-8) | | |
| ISOBUTANE (CAS 75-28 | | |
| PROPANE (CAS 74-98-6 SARA 304 Emergency releas | | |
| Not regulated. | | |
| 5 | d Substances (29 CFR 1910.1001-1052) | |
| Not regulated. | | |
| - | authorization Act of 1986 (SARA) | |
| SARA 302 Extremely hazard Not listed. | ous substance | |
| SARA 311/312 Hazardous chemical | No (Exempt) | |
| SARA 313 (TRI reporting) Not regulated. | | |
| Other federal regulations | | |
| Clean Air Act (CAA) Section | 112 Hazardous Air Pollutants (HAPs) List | |
| Not regulated. Clean Air Act (CAA) Section | 112(r) Accidental Release Prevention (40 CFR 68.130) | |
| BUTANE (CAS 106-97-8) ISOBUTANE (CAS 75-28 PROPANE (CAS 74-98-6 | -5) | |
| Safe Drinking Water Act (SDWA) | Not regulated. | |
| FEMA Priority Substanc GLYCERIN (CAS 56 | es Respiratory Health and Safety in the Flavor Manufacturing -81-5) Other Flavoring Substances with | - |
| , | uding date of preparation or last revision | |
| Issue date | 12-03-2021 | |
| Version # | 01 | |
| NFPA ratings | Health: 0 | |
| - | Flammability: 4 Instability: 0 | |

Material name: L'ORÉAL PROFESSIONNEL SERIE EXPERT CURL IDENTITY MOUSSE 10-IN-1 1247535 B Version #: 01 Issue date: 12-03-2021

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.