SAFETY DATA SHEET

1. Identification

Product identifier	BIOLAGE STYLING WHIPPED VOLUME MOUSSE	
Other means of identification		
SDS number	21-91-0000105	
Recommended use	Personal care product used for cosmetic effect.	
Recommended restrictions	None known.	
Manufacturer/Importer/Supplier/Distributor information		
US Address:	L'Oreal USA Products, Inc	
	133 Terminal Avenue	
	Clark, NJ 07066	
	USA	
Canadian Address:	L'Oreal Canada	
	4895 rue Hickmore	
	Ville St-Laurent, H4T 1K5	
	Canada	
Emergency Phone # :	1-800-535-5053 (International: 352-323-3500)	
	In Canada - 1-613-996-6666 (Canutec (*666 Cellular))	
For further Information:	1-732-499-2741	
Poison Control # :	412-390-3326	

2. Hazard(s) identification

Physical hazards	Flammable aerosols	Category 1
	Gases under pressure	Liquefied gas
Health hazards	Not classified.	
OSHA defined hazards	Not classified.	
Label elements		

Signal word	Danger	
Hazard statement	Extremely flammable aerosol. Contains gas under pressure; may explode if heated.	
Precautionary statement		
Prevention	Keep away from heat/sparks/open flames/hot surfaces No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use.	
Response	Wash hands after handling.	
Storage	Protect from sunlight. Store in a well-ventilated place. Do not expose to temperatures exceeding 50°C/122°F.	J
Disposal	Dispose of waste and residues in accordance with local authority requirements.	
Hazard(s) not otherwise classified (HNOC)	None known.	
Supplemental information	None.	

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
DIMETHYL ETHER		115-10-6	2.7
ISOBUTANE		75-28-5	2.38
PROPANE		74-98-6	0.42

*Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

4. First-aid measures

Inhalation	Move to fresh air. Call a physician if symptoms develop or persist.	
Skin contact	No adverse effects due to skin contact are expected.	
Eye contact	No specific first aid measures noted.	
Ingestion	Not likely, due to the form of the product. In the unlikely event of swallowing contact a physician or poison control center.	
Most important symptoms/effects, acute and delayed	Not available.	
Indication of immediate medical attention and special treatment needed	Provide general supportive measures and treat symptomatically.	
General information	Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.	
5. Fire-fighting measures		
Suitable extinguishing media	Water fog. Foam. Dry chemical powder. Carbon dioxide (CO2).	
Unsuitable extinguishing media	Do not use water jet as an extinguisher, as this will spread the fire.	
Specific hazards arising from the chemical	Contents under pressure. Pressurized container may explode when exposed to heat or flame. During fire, gases hazardous to health may be formed.	
Special protective equipment and precautions for firefighters	Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.	
Fire fighting equipment/instructions	In case of fire: Stop leak if safe to do so. Do not move cargo or vehicle if cargo has been exposed to heat. Move containers from fire area if you can do so without risk. Containers should be cooled with water to prevent vapor pressure build up. For massive fire in cargo area, use unmanned hose holder or monitor nozzles, if possible. If not, withdraw and let fire burn out.	
Specific methods	Use standard firefighting procedures and consider the hazards of other involved materials. Move containers from fire area if you can do so without risk. In the event of fire and/or explosion do not breathe fumes.	
General fire hazards	Extremely flammable aerosol. Contents under pressure. Pressurized container may explode when exposed to heat or flame.	

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures	Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Keep out of low areas. Many gases are heavier than air and will spread along ground and collect in low or confined areas (sewers, basements, tanks). Wear appropriate protective equipment and clothing during clean-up. Emergency personnel need self-contained breathing equipment. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.
Methods and materials for containment and cleaning up	Refer to attached safety data sheets and/or instructions for use. Stop leak if you can do so without risk. Move the cylinder to a safe and open area if the leak is irreparable. Isolate area until gas has dispersed. Keep combustibles (wood, paper, oil, etc.) away from spilled material. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water.
Environmental precautions	Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination. For waste disposal, see section 13 of the SDS. Avoid discharge into drains, water courses or onto the ground.

7. Handling and storage

Precautions for safe handling	Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. All equipment used when handling the product must be grounded. Close valve after each use and when empty. Protect containers from physical damage; do not drag, roll, slide, or drop. When moving containers, even
	for short distances, use a cart (trolley, hand truck, etc.) designed to transport containers. Suck back of water into the container must be prevented. Do not allow backfeed into the container. Purge air from system before introducing gas. Use only properly specified equipment which is suitable for this product, its supply pressure and temperature. Contact your gas supplier if in doubt. Do not re-use empty containers. Avoid prolonged exposure. Use only in well-ventilated areas. Wear appropriate personal protective equipment. Observe good industrial hygiene practices.
Conditions for safe storage,	Level 1 Aerosol.
including any incompatibilities	Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C/122 °F. Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. This material can accumulate static charge which may cause spark and become an ignition source. Store in tightly closed container. Store in a well-ventilated place. Stored containers should be periodically checked for general condition and leakage. Keep out of the reach of children. Store away from incompatible materials (see Section 10 of the SDS).
8. Exposure controls/pers	onal protection

Occupational exposure limits

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit. At this time, the other constituents have no known exposure limits.

Components	Туре	Value
PROPANE (CAS 74-98-6)	PEL	1800 mg/m3
		1000 ppm
US. ACGIH Threshold Limit	Values	
Components	Туре	Value
ISOBUTANE (CAS 75-28-5)	STEL	1000 ppm
US. NIOSH: Pocket Guide to	Chemical Hazards	
Components	Туре	Value
ISOBUTANE (CAS 75-28-5)	TWA	1900 mg/m3
		800 ppm
PROPANE (CAS 74-98-6)	TWA	1800 mg/m3
		1000 ppm
US. Workplace Environment	tal Exposure Level (WEEL) Guides	1000 ppm
US. Workplace Environment Components	tal Exposure Level (WEEL) Guides Type	1000 ppm Value
-	,	
Components DIMETHYL ETHER (CAS	Туре	Value
Components DIMETHYL ETHER (CAS	Туре	Value 1880 mg/m3 1000 ppm
Components DIMETHYL ETHER (CAS 115-10-6)	Type TWA No biological exposure limits noted fo Good general ventilation should be u applicable, use process enclosures, l	Value 1880 mg/m3 1000 ppm or the ingredient(s). sed. Ventilation rates should be matched to conditions. If ocal exhaust ventilation, or other engineering controls to mended exposure limits. If exposure limits have not been
Components DIMETHYL ETHER (CAS 115-10-6) ogical limit values propriate engineering trols	Type TWA No biological exposure limits noted fo Good general ventilation should be u applicable, use process enclosures, l maintain airborne levels below recom established, maintain airborne levels such as personal protective equipm	Value 1880 mg/m3 1000 ppm or the ingredient(s). sed. Ventilation rates should be matched to conditions. If ocal exhaust ventilation, or other engineering controls to imended exposure limits. If exposure limits have not been to an acceptable level.
Components DIMETHYL ETHER (CAS 115-10-6) logical limit values propriate engineering trols	Type TWA No biological exposure limits noted fo Good general ventilation should be u applicable, use process enclosures, l maintain airborne levels below recom established, maintain airborne levels such as personal protective equipm Applicable for industrial settings only	Value 1880 mg/m3 1000 ppm or the ingredient(s). sed. Ventilation rates should be matched to conditions. If ocal exhaust ventilation, or other engineering controls to imended exposure limits. If exposure limits have not been to an acceptable level. ent

Respiratory protection	Applicable for industrial settings only. If permissible levels are exceeded use NIOSH mechanical filter / organic vapor cartridge or an air-supplied respirator.
Thermal hazards	Wear appropriate thermal protective clothing, when necessary.
General hygiene considerations	When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

9. Physical and chemical properties

Appearance	
Physical state	Liquid.
Form	Aerosol.
Color	Not available.
Odor	Characteristic.
Odor threshold	Not available.
рН	Not available.
Melting point/freezing point	Not available.
Initial boiling point and boiling range	Not available.
Flash point	Not available.
Evaporation rate	Not available.
Flammability (solid, gas)	Not applicable.
Upper/lower flammability or expl	osive limits
Flammability limit - lower (%)	Not available.
Flammability limit - upper (%)	Not available.
Explosive limit - lower (%)	Not available.
Explosive limit - upper (%)	Not available.
Vapor pressure	Not available.
Vapor density	Not available.
Relative density	Not available.
Solubility(ies)	
Solubility (water)	Not available.
Partition coefficient (n-octanol/water)	Not available.
Auto-ignition temperature	Not available.
Decomposition temperature	Not available.
Viscosity	Not available.
Other information	
Explosive properties	Not explosive.
Heat of combustion	5.54 kJ/g
Oxidizing properties	Not oxidizing.

10. Stability and reactivity

Reactivity	The product is stable and non-reactive under normal conditions of use, storage and transport.
Chemical stability	Material is stable under normal conditions.
Possibility of hazardous reactions	No dangerous reaction known under conditions of normal use.
Conditions to avoid	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. Contact with incompatible materials.
Incompatible materials	Strong oxidizing agents.
Hazardous decomposition products	No hazardous decomposition products are known.

11. Toxicological information

Information on likely routes of exposure

Information on likely routes of e	•		
Inhalation	Prolonged inhalation may be harmful.		
Skin contact	No adverse effects due to skin contact are expected.		
Eye contact	No adverse effects due to eye contact are expected.		
Ingestion	Expected to be a low ingestion hazard.		
Symptoms related to the physical, chemical and toxicological characteristics	Not available.		
Information on toxicological effe	ects		
Acute toxicity	Not known.		
Product	Species	Test Results	
BIOLAGE STYLING WHIPPED VC	DLUME MOUSSE		
<u>Acute</u> Oral ATEmix		552500 mg/kg	
Components	Species	Test Results	
DIMETHYL ETHER (CAS 115-10-0			
<u>Acute</u> Inhalation Gas LC50	Rat	164000 ppm, 4 h	
Skin corrosion/irritation			
Skin conosion/initiation	skin contact are expected.	c of data the classification is not possible. No adverse effects due to	
Irritation Corrosion - Sk DIMETHYL ETHER		Result: Contact with liquid form may cause frostbite.	
Serious eye damage/eye irritation	Due to partial or complete lack eye contact are expected.	c of data the classification is not possible. No adverse effects due to	
Irritation Corrosion - Ey DIMETHYL ETHER	e	Result: Contact with liquid form may cause frostbite.	
Respiratory or skin sensitization			
Respiratory sensitization		of data the classification is not possible.	
Skin sensitization		of data the classification is not possible.	
Germ cell mutagenicity	Due to partial or complete lack	of data the classification is not possible.	
Mutagenicity DIMETHYL ETHER		Result: In vitro and in vivo tests did not show mutagenic effects.	
Carcinogenicity	Not classifiable as to carcinog classification is not possible.	enicity to humans. Due to partial or complete lack of data the	
IARC Monographs. Overall E	Evaluation of Carcinogenicity		
Not listed. OSHA Specifically Regulate	d Substances (29 CFR 1910.10	001-1052)	
Not regulated. US. National Toxicology Pro Not listed.	gram (NTP) Report on Carcin	ogens	
Reproductive toxicity	Due to partial or complete lack	of data the classification is not possible.	
Developmental effects			
DIMETHYL ETHER		40000 ppm OECD 414 Result: NOAEL Species: Rat	
Reproductivity DIMETHYL ETHER		2.5 % OECD 452, No effects on fertility Result: NOAEL Species: Rat	

Specific target organ toxicity - single exposure	Due to partial or complete lack of data the classification is not possible.			
Specific target organ toxicity - repeated exposure	Due to partial or complete lack of data the classification is not possible. 47106 mg/m3 air OECD 452, Inhalation Result: NOAEC Species: Rat Test Duration: 2 yr			
DIMETHYL ETHER				
Aspiration hazard	Due to pa	rtial or complete lack of data the cla	assification is not possible.	
Further information	The reference to any animal testing for individual constituents mentioned in this document is based on public, third-party data.			
12. Ecological information	า			
Ecotoxicity	The product is not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.			
Components		Species	Test Results	
DIMETHYL ETHER (CAS 11	5-10-6)			
Aquatic				
Acute	5050			
Algae	EC50	Green algae	154.917 mg/l, 96 h QSAR	
Crustacea	EC50	Daphnia magna	> 4400 mg/l, 48 h	
Fish	LC50	Poecilia reticulata	> 4100 mg/l, 96 h	
Other	EC10	Pseudomonas putida	> 1600 mg/l	
Persistence and degradability Biodegradability Percent degradation (A DIMETHYL ETHER	erobic biod	5 % OECD 30	eadily Biodegradable	
Bioaccumulative potential				
Partition coefficient n-octai DIMETHYL ETHER ISOBUTANE PROPANE	nol / water (I	og Kow) 0.1 2.76 2.36		
Mobility in soil	No data a	vailable.		
Other adverse effects	No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.			
13. Disposal consideratio	ns			
Disposal instructions	Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Contents under pressure. Do not puncture, incinerate or crush. Dispose of contents/container in accordance with local/regional/national/international regulations.			
Local disposal regulations	Dispose in accordance with all applicable regulations.			
Hazardous waste code	This produ	uct is ignitable (D001) RCRA hazar	dous wastes when intended for disposal.	
Waste from residues / unused products	Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).			
Contaminated packaging	Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal. Do not re-use empty containers.			
14. Transport information				
DOT				
FINISHED GOODS				
LINL as seen to a state				

FINISHED GOODS	
UN number	UN1950
UN proper shipping name	AEROSOLS, FLAMMABLE, Limited Quantity
Class	2.1
Packing group	Not applicable.

Transport hazard class(es)						
Label(s)	Limited Quantity					
Packaging exceptions BULK	306					
Not regulated as dangerous g						
IATA	0003.					
FINISHED GOODS						
UN number	ID8000					
UN proper shipping name	CONSUMER COMMODITY					
Class	9 - Class 9					
Packing group	Not applicable.					
Transport hazard class(es)						
Label(s) ERG Number	Class 9, Limited Quantity 9L					
LTD QTY Net Inner Capacity						
BULK						
Not regulated as dangerous g	oods.					
IMDG						
FINISHED GOODS						
UN number	UN1950					
UN proper shipping name	AEROSOLS, FLAMMABLE, Limited Quantity					
Class Packing group	2.1 Not applicable.					
Environmental Hazards						
Marine pollutant	No.					
Transport hazard class(es)						
Label(s)	Limited Quantity					
EmS	F-D, S-U					
BULK						
Not regulated as dangerous g						
General information	Avoid transport on vehicles where the load space is not separated from the driver's compartment. Ensure vehicle driver is aware of the potential hazards of the load and knows what to do in the event of an accident or an emergency. Before transporting product containers: Ensure that containers are firmly secured. Ensure cylinder valve is closed and not leaking. Ensure valve outlet cap nut or plug (where provided) is correctly fitted. Ensure valve protection device (where provided) is correctly fitted. Ensure adequate ventilation. Ensure compliance with applicable regulations.					
15. Regulatory information	n					
US federal regulations	This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.					
Toxic Substances Control A	loct (TSCA)					
TSCA Section 12(b) Exp	oort Notification (40 CFR 707, Subpt. D)					
Not regulated.						
CERCLA Hazardous Substa	nce List (40 CFR 302.4)					
DIMETHYL ETHER (CAS ISOBUTANE (CAS 75-28 PROPANE (CAS 74-98-6	B-5) Listed. b) Listed.					
SARA 304 Emergency relea	se notification					
	d Substances (29 CFR 1910.1001-1052)					
Not regulated.						
Superfund Amendments and Re SARA 302 Extremely hazard Not listed.	authorization Act of 1986 (SARA) lous substance					
SARA 311/312 Hazardous chemical	No (Exempt)					

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

DIMETHYL ETHER (CAS 115-10-6) ISOBUTANE (CAS 75-28-5) PROPANE (CAS 74-98-6)

Safe Drinking Water Act Not regulated. (SDWA)

16. Other information, including date of preparation or last revision

Issue date	02-20-2020
Version #	01
NFPA ratings	Health: 0 Flammability: 4 Instability: 0
Disclaimer	The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.