SAFETY DATA SHEET

Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II, as amended by Regulation (EU) No. 2015/830

MOROCCANOIL COLOR CALYPSO DEMI-PERMANENT CREAM COLOR 10.13

Date: 28 Jul 2022

Vers: 0

SECTION 1: Identification of the substance / mixture and of the company / undertaking

1.1 Product identifier

Product description: MOROCCANOIL COLOR CALYPSO DEMI-PERMANENT CREAM COLOR 10.13 Product code: PF025786-CI024241

1.2 Relevant identified uses of the substance or mixture

cosmetic product

1.3 Details of the supplier of the safety data sheet

BEAUTY & BUSINESS S.P.A. Via Ciserano, snc. - 24046 Osio Sotto (BG) - ITALY Tel.: 035 4197798 Fax: 035 4197734 e-mail: schede.sicurezza@alfaparfgroup.it

1.4 Emergency telephone number

BEAUTY & BUSINESS S.P.A. Tel.: 035 4197798 (office hours)

SECTION 2: Hazard identification

2.1 Classification of the substance/mixture according to (EC) 1272/2008

/ Eye Dam. 1

2.2 Label according to (EC) 1272/2008

Pictogram:



Signal Word:

Danger

Hazard statement:

EUH208 Contains TOLUENE-2,5-DIAMINE SULFATE may produce an allergic reaction

H318 Causes serious eye damage

Precautionary statement (Prevention)

P280 Wear protective gloves/protective clothing/eye protection/face protection

Precautionary statement (Response)

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P310 Immediately call a POISON CENTER or doctor/physician.

2.3 Additional hazards

None known

SECTION 3: Composition / informations on ingredients

3.1 Substances:

Not applicable

3.2 Mixture:

5-7 % ARGININE

CAS#: 74-79-3 EINECS#: 200-811-1 Eye Irrit. 2 H319

3-5 % LAURETH-3

Eye Irrit. 1 H318 – Aquatic Chronic 3 H412 – Aquatic Tox. 1 H400 – Fattore M: 1

CAS#: 3055-94-5 EINECS#: 221-280-2

1-3 % OLEYL PHOSPHATE

Eye Dam. 1 H318

CAS#: 37310-83-1 EINECS#: 253-455-4

1-3 % COCAMIDOPROPYL BETAINE

Eye Dam. 1 H318 – Aquatic Chronic 3 H412

CAS#: 61789-40-0 EINECS#: 263-058-8

< 1 % TOLUENE-2,5-DIAMINE SULFATE Acute Tox. 3 H301 – Aquatic Chronic 2 H411 – Acute Tox. 4 H312 – Acute Tox. 4 H332 – Skin Sens. 1 H317 CAS#: 615-50-9 EINECS#: 210-431-8

< 1 % POTASSIUM HYDROXIDE

Acute Tox. 4 H302 – Skin Corr. 1A H314 – Met. Corr. 1 H290

CAS#: 1310-58-3 EINECS#: 215-181-3

< 1 % POLYQUATERNIUM-22

CAS#: 53694-17-0 EINECS#:

- Aquatic Chronic 3 H412
- < 1 % OLETH-4 PHOSPHATE

Skin Irrit. 2 H315

- CAS#: 39464-69-2 EINECS#:
- < 1 % ERYTHORBIC ACID
 - Eye Irrit. 2 H319 STOT SE 3 H335 Skin Irrit. 2 H315

CAS#: 89-65-6 EINECS#: 201-928-0

< 1 % EDTA

Eye Irrit. 2 H319 – Acute Tox. 4 H332 – STOT RE 2 H373

CAS#: 60-00-4 EINECS#: 200-449-4

< 1 % C12-13 PARETH-9

CAS#: 66455-14-9 EINECS#:

Eye Irrit. 2 H319

SECTION 4: First aid measures

4.1 Description of first aid measures

Inhalation

Move victim to a well-ventilated place or into fresh air; in case of malaise get medical advice.

Skin contact

Wash off with plenty of water. Change clothing if necessary. If irritation persists, or tissue damage shows, seek for medical advice.

Eye contact

Flush eyes under running water for a few minutes, keeping eyelids well opened. If pain persists, seek for medical advice.

Ingestion

Do not induce vomiting, unless after obtaining medical authorization to do so. Never give anything by mouth to an unconscious person. Consult a physician, showing the safety data sheet.

4.2 Main symptoms

Symptoms and effects known are reported in Section 2 and/or Section 11. Other effects are possible.

4.3 Indications for medical intervention and / or specific treatments

Treatments: symptomatic treatment.

SECTION 5: Fire fighting measures

5.1 Extinguishing media

Water, CO2, foam, dry powder, depending on the materials affected by the fire.

5.2 Special hazards by the product/itself

In case of fire, carbon oxides can be released. In some case, if fire occurs, some dangerous combustion products can be released.

5.3 Advice for fire-fighters

Avoid breathing fumes.

Wear self-contained breathing apparatus if necessary.

SECTION 6: Accidental release measures

6.1 Personal precautions, protection equipment and emergency procedures:

Wear self-contained breathing apparatus, gloves and protective clothes. Refer to Section 8.

6.2 Environmental precautions

Limit leakages and spillage with sand or soil.

6.3 Methods e materials for containment

Quickly collect the product wearing protective mask and clothing.

If the product is in a liquid form, prevent it goes into the sewer system. Collect the product for re-use if possible, or for the disposal. Eventually absorb with inert material.

After collecting residues, wash interested zone and materials with water.

6.4 Reference to other sections

Where appropriate, reference is made to sections 8 and 13.

SECTION 7: Handling and storage

For transport, storage and handling only use suitable materials.

7.1 Precautions for safe handling

Handle in accordance with good industrial hygiene and safety practice.

Avoid contact and inhalation of vapours. See also paragraph 8.

When using do not eat or drink.

7.2 Conditions for safe storage, including any incompatibilities

Store in a cool and dry place. Avoid direct exposure to the sun. Keep away from open flames, sparks and other sources of ignition. No smoking. Make sure there is adequate ventilation.

7.3 Specific final uses

No data available

SECTION 8: Exposure controls / personal protection

8.1 Control parameters

No data available

8.2 Exposure control

Personal protective equipment

General protective and hygienic measures.

At work do not eat, drink or smoke. Use of appropriate protection measures for hands, eyes, skin and respiratory system. The manufacturer of the protective equipment should ensure that the means are appropriate to the concerned product.

Respiratory protection

If threshold value for daily exposure in the workplace is exceeded, wear a half-mask type FFP3 (ref. STANDARD EN 141). In the case the substance is odorless or its olfactory threshold is higher than the relative exposure limit, or in case of

emergency, i.e. when exposure levels are unknown or the concentration of oxygen in the workplace is less than 17% volume, wear a compressed air breathing apparatus (EN 137) or fresh air hose breathing apparatus for use with full face mask, half mask or mouthplece (EN 138).

Hand protection

Protect your hands with gloves category II (ref. Dir. 89/686 / EEC and standard EN 374) such as PVC, nitrile, neoprene or equivalent.

Eye protection

Safety glasses with side shields (EN 166).

Additional information about design of technical facilities

Workplace must be adequately ventilated. Where possible, install localized air intake system and effective system for general air exchange.

If these measures are not sufficient to maintain concentrations of particulates and solvent vapors below the exposure limit, you will need to make use of appropriate respiratory protection.

SECTION 9: Physical and chemical properties

| Aspect: | Emulsion |
|-----------------------|----------------|
| Colour: | Beige to Ivory |
| Odour: | Characteristic |
| Density: | 0,975 - 1,015 |
| Dry content (110 °C): | 33,00 - 39,00 |

pH:

9,00 - 10,50

Viscosity, dynamic:

Flash point:

SECTION 10: Stability and reactivity

10.1 Reactivity

There are no data available on the product itself.

10.2 Chemical stability

The product is stable in normal conditions of use and storage (refer to paragraph 7).

10.3 Possibility of hazard reactions

None relevant.

10.4 Conditions to avoid

Avoid high temperatures. Keep the product away from open flames. Avoid to expose the container to the direct sunlight.

10.5 Incompatible materials

Strong acids, strong oxidants.

10.6 Hazardous decomposition products

The combustion can release carbon oxides.

SECTION 11: Toxicological informations

No toxicological data available on the product itself. Consider then, the concentration of each substance in assessing the toxicological effects deriving from the preparation.

11.1 Information on toxicological effects

Set out below is the toxicological information relating to the main substances in the preparation:

EDTA

LD 50 Oral rat: 2000 mg/Kg ERYTHORBIC ACID LD 50 Oral rat: 18000 mg/Kg LAURETH-3 LD 50 Oral rat: 5000 mg/Kg POLYQUATERNIUM-22 LD 50 Oral rat: 5000 mg/Kg POTASSIUM HYDROXIDE LD 50 Oral rat: 333 mg/Kg TOLUENE-2,5-DIAMINE SULFATE LD 50 Oral rat: 102 mg/Kg

SECTION 12: Ecological informations

Adopt good working practices, avoiding littering.

12.1 Toxicity

EDTA

LC 50: 100 mg/l/96h

LAURETH-3

LC 50: 10 mg/l/96h POLYQUATERNIUM-22 LC 50: 100 mg/l/96h POTASSIUM HYDROXIDE LC 50: 96 mg/l/96h

12.2 Persistence

No data available.

12.3 Bioaccumulative potential

No data available.

12.4 Motility in soil

No data available.

12.5 Results of PBT e vPvB assessment

No data available.

12.6 Other adverse effects

No data available.

SECTION 13: Disposal consideration

13.1 Methods of treatment of the waste

Operate in compliance with local and national regulations.

Contaminated packaging

Collect all residues and contaminated packaging. After an appropriate cleaning, packaging can be recycled. Uncleaned packaging must be disposed of under the same requirements of the product.

| 14.1 UN Number: Non Hazardous | |
|------------------------------------|---|
| Non Hazardous | |
| | |
| 14.2 UN Proper Shipping Name: | |
| Non Hazardous | |
| 14.3 Transport Hazard Class(es): | |
| Non Hazardous | |
| 14.4 Packaging Group: | |
| Non Hazardous | |
| 14.5 Environmental Hazards | |
| Marine pollutant: | / |
| 14.6 Special Precautions for Users | |
| (ADR) Tunnel Restriction Code: | / |
| (IMDG) EmS Number: | / |
| (IMDG) Stowage and Segregation: | / |

SECTION 15: Regulatory informations

15.1 Regulations

Regulation (EC) 1907/2006 (REACH) and following amendments

Regulation (EC) 1272/2008 (CLP) and following amendments

Regulation (EC) 1223/2009 (Cosmetic Regulation) and following amendments

In the EU, finished cosmetic products are exempted from any obligation of classification and hazard labeling, as well as from provisions concerning safety data sheets [(Reg. (EC) 1907/2006, art. 2, comma 6, letter b) and Reg. (EC) 1272/2008 art. 1, comma 5, letter c)].

15.2 Evaluation of chemical security

No data available

SECTION 16: Other informations

The data contained in this safety data sheet are based on our current knowledge and experience at the date indicated above.

The user must verify the suitability and completeness of such information, in relation to the particular use intended.

This safety data sheet cancels and replaces any previous releases of the same.

According to Regulation (EC) N° 1907/2006 (REACH) with its amendment Regulation (EC) N° 2015/830

Sources of Key Data:

Regulation (EC) N° 1272/2008 and Regulation (EC) N° 1907/2006, with following amendments

Full text of hazard categories and H and EUH statements:

| H314 | Causes severe skin burns and eve damage |
|---------------------|--|
| H315 | Causes skin pritation |
| | |
| H317 | May cause an allergic skin reaction |
| H318 | Causes serious eye damage |
| H319 | Causes serious eye irritation |
| H332 | Harmful if inhaled |
| H335 | May cause respiratory irritation |
| H341 | Suspected of causing genetic defects (state route of exposure if it is conclusively proven that no other routes of exposure cause the hazard) |
| H373 | May cause damage to organs (state all organs affected, if known) through prolonged or repeated exposure (state route of exposure if it is conclusively proven that no other routes of exposure cause the hazard) |
| H400 | Very toxic to aquatic life |
| H410 | Very toxicto aquatic lifewith long lastingeffects |
| H411 | Toxic to aquatic life with long-lasting effects |
| H412 | Harmful to aquatic life with long-lasting effects |
| Acute Tox. 3 | Acute toxicity (oral) Cat. 3 |
| Acute Tox. 4 | Acute toxicity (dermal) Cat. 4 |
| Acute Tox. 4 | Acute toxicity (inhalation) Cat. 4 |
| Acute Tox. 4 | Acute toxicity (oral) Cat. 4 |
| Aquatic Acute 1 | Hazardous to the aquatic environment - acute toxicity Cat. 1 |
| Aquatic Chronic 1 | Hazardous to the aquatic environment - chronic toxicity Cat. 1 |
| Aquatic Chronic 2 | Hazardous to the aquatic environment - chronic toxicity Cat. 2 |
| Aquatic Chronic 3 | Hazardous to the aquatic environment - chronic toxicity Cat. 3 |
| Eye Dam. 1 | Serious eye Damage Cat. 1 |
| Eye Irrit. 2 | Eye irritation Cat. 2 |
| Flam. Liq. 3 | Flammable liquid Cat. 3 |
| Met. Corr. 1 | Substances and mixtures corrosive to metals Cat. 1 |
| Muta. 2 | Germ cell mutagenicity Cat. 2 |
| Skin Corr. 1A/1B/1C | Skin Corrosion Cat. 1A/1B/1C |

| Skin Irr. 2 | Skin irritation Cat. 2 |
|----------------|------------------------------|
| Skin Sens. 1 | Skin Sensitization Cat. 1 |
| STOT RE Cat. 2 | STOT RE Cat. 2 |
| STOT SE Cat. 3 | STOT SE Cat. 3 |
| H226 | Flammable liquid and vapour |
| H290 | May be corrosive to metals |
| H301 | Toxic if swallowed |
| H302 | Harmful if swallowed |
| H312 | Harmful in contact with skin |

Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:

| / | EUH208 | Calculation method |
|------------|--------|--------------------|
| Eye Dam. 1 | H318 | Calculation method |

Acronyms:

| ADR | Accord européen relatif au transport international des merchandises Dangereuses par Route |
|---------------|---|
| CAS | Chemical Abstracts Service |
| CLP | Classification, Labelling and Packaging |
| EC | European Community |
| EEC | European Economic Community |
| EINECS | European Inventory of Existing Commercial Chemical Substances |
| EN | European Norm |
| EU | European Union |
| FFP | Filtering Facepiece |
| ΙΑΤΑ | International Air Transport Association |
| IMDG | International Maritime Dangerous Goods |
| LD (0/50/100) | Lethal Dose (0/50/100) |
| N.A. | Not Applicable |
| N.D. | No Date |
| РВТ | Persistent, Bioaccumulative and Toxic |
| PVC | PolyVinylChloride |
| REACH | Registration, Evaluation, Authorisation and Restriction of Chemical Substances |
| UN | United Nations |
| vPvB | very Persistent very Bioaccumulative |