

MATERIAL SAFETY DATA SHEET

Oster Kool-Lube 3

Section 1: PRODUCT AND COMPANY IDENTIFICATION

Product Name: Oster Kool-Lube 3
Product Number: A07146
Product Use: Lubricant.
Manufacturer/Supplier: Oster Professional Products / Sunbeam Product Inc., D/B/A Jarden Consumer Solutions
150 Cadillac Lane,
McMinnville, TN 37110
Phone Number: Oster Customer Service (800) 339-2547 (CST) 8AM- 5PM
Safety Questions: (888)-865-6810 (CST) 7 AM-5:30 PM
D.O.T. Emergency Phone: CHEM TEL (800) 255-3924
Date of Preparation: August 15, 2011 **Revision #:** 3.0

Section 2: HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

HMIS: See Section 15

CAUTION

MAY CAUSE EYE IRRITATION. MAY CAUSE SKIN IRRITATION. CONTENTS UNDER PRESSURE. CONTAINER MAY EXPLODE IF HEATED.

Potential Health Effects: See Section 11 for more information.

Likely Routes of Exposure: Skin contact, eye contact, inhalation, and ingestion.

Eye: May cause eye irritation.
Skin: May cause skin irritation.
Ingestion: Not a normal route of exposure. Harmful: may cause lung damage if swallowed.
Inhalation: May cause respiratory tract irritation. This product may be aspirated into the lungs and cause chemical pneumonitis.

Chronic Effects: Prolonged or repeated contact may dry skin and cause irritation.

Signs and Symptoms: Symptoms may include discomfort or pain, excess blinking and tear production, with possible redness and swelling. Symptoms may include redness, drying, and cracking of the skin. Vapours may cause drowsiness and dizziness.

Medical Conditions Aggravated By Exposure: Asthma. Allergies.

Target Organs: Skin, eyes, gastrointestinal tract, respiratory system.

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

Potential Environmental Effects: May cause long-term adverse effects in the aquatic environment. See Section 12 for more information.

Section 3: COMPOSITION / INFORMATION ON INGREDIENTS

Ingredient	CAS #	Wt. %
Ethanol	64-17-5	30 - 60
Isobutane	75-28-5	10 - 30
Propane	74-98-6	7 - 13
Triethylene glycol	112-27-6	3 - 7
Isopropanol	67-63-0	1 - 5

MATERIAL SAFETY DATA SHEET

Oster Kool-Lube 3

Section 4: FIRST AID MEASURES

- Eye Contact:** In case of contact, immediately flush eyes with plenty of water. If easy to do, remove contact lenses, if worn.
- Skin Contact:** In case of contact, immediately flush skin with plenty of water. Remove contaminated clothing and shoes. Wash clothing before reuse. Call a physician if irritation develops and persists.
- Inhalation:** If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen.
- Ingestion:** If swallowed, do NOT induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person.
- General Advice:** In case of accident or if you feel unwell, seek medical advice immediately (show the label or MSDS where possible).
- Note to Physicians:** Symptoms may not appear immediately.

Section 5: FIRE FIGHTING MEASURES

- Flammability:** Not flammable by OSHA criteria.
- Means of Extinction:**
- Suitable Extinguishing Media:** Powder, water spray, foam, carbon dioxide.
- Unsuitable Extinguishing Media:** Not available.
- Products of Combustion:** May include, and are not limited to: oxides of carbon, oxides of nitrogen.
- Explosion Data:**
- Sensitivity to Mechanical Impact:** Not available.
- Sensitivity to Static Discharge:** Not available.
- Protection of Firefighters:** Containers may explode when heated. Keep upwind of fire. Wear full fire fighting turn-out gear (full Bunker gear) and respiratory protection (SCBA).

Section 6: ACCIDENTAL RELEASE MEASURES

- Personal Precautions:** Use personal protection recommended in Section 8. Isolate the hazard area and deny entry to unnecessary and unprotected personnel. Eliminate sources of ignition. Ruptured cylinders may rocket.
- Environmental Precautions:** Many gases are heavier than air and will spread along ground and collect in low or confined areas (sewers, basements, tanks). This material is a water pollutant. Keep out of drains, sewers, ditches, and waterways. Minimize use of water to prevent environmental contamination.
- Methods for Containment:** Contain and/or absorb spill with inert material (e.g. sand, vermiculite), then place in a suitable container. Do not flush to sewer or allow to enter waterways. Use appropriate Personal Protective Equipment (PPE).
- Methods for Clean-Up:** Soak into absorbent material. Spills of this material are a slipping hazard. Thoroughly wash the area with water after a spill or leak.
- Other Information:** Not available.

MATERIAL SAFETY DATA SHEET

Oster Kool-Lube 3

Section 7: HANDLING AND STORAGE

Handling:

Keep away from sources of ignition. No smoking. Avoid contact with skin and eyes. Do not swallow. Do not breathe gas/fumes/vapor/spray. Use only in well-ventilated areas. When using do not eat or drink. Wash hands before eating, drinking, or smoking.

Storage:

Keep out of the reach of children. Keep container tightly closed and in a well-ventilated place. Do not store at temperatures above 49 °C / 120 °F.

Section 8: EXPOSURE CONTROLS / PERSONAL PROTECTION

Exposure Guidelines

Ingredient	Exposure Limits	
	OSHA-PEL	ACGIH-TLV
Ethanol	1000 ppm	1000 ppm
Isobutane	Not available.	Not available.
Propane	1000 ppm	1000 ppm
Triethylene glycol	Not available.	Not available.
Isopropanol	400 ppm	200 ppm

Engineering Controls: Use ventilation adequate to keep exposures (airborne levels of dust, fume, vapor, etc.) below recommended exposure limits.

Personal Protective Equipment:

HMIS: See Section 15

Eye/Face Protection: Wear eye/face protection.

Hand Protection: Wear suitable gloves.

Skin and Body Protection: Wear suitable protective clothing.

Respiratory Protection: In case of insufficient ventilation, wear suitable respiratory equipment.

General Hygiene Considerations: Handle according to established industrial hygiene and safety practices.

Section 9: PHYSICAL AND CHEMICAL PROPERTIES

Appearance:	Clear.
Color:	Colorless.
Odour:	Lemon/Alcohol.
Odour Threshold:	Not available.
Physical State:	Liquid.
pH:	10.4
Viscosity:	Not available.
Freezing Point:	Not available.
Boiling Point:	Not available.
Flash Point:	Not available.
Evaporation Rate:	> 1 (Water = 1)
Lower Flammability Limit:	Not available.
Upper Flammability Limit:	Not available.

MATERIAL SAFETY DATA SHEET

Oster Kool-Lube 3

Vapor Pressure:	PSIG @ 21°C (70°F) (Aerosols): Max.60
Vapor Density:	> 1 (Air = 1)
Specific Gravity:	0.842 (Concentrate only)
Solubility in Water:	Complete.
Coefficient of Water/Oil Distribution:	Not available.
Auto-ignition Temperature:	Not available.
Percent Volatile, wt. %:	Not available.
VOC content, wt. %:	86.6% (US federal/CARB/OTC/LADCO)
VOC content, g/L:	Not available.

Section 10: STABILITY AND REACTIVITY

Stability: Stable under normal storage conditions. Contents under pressure. Container may explode if heated. Do not puncture. Do not burn. Keep in a cool place.

Conditions of Reactivity: Heat. Incompatible materials.

Incompatible Materials: Oxidizers. Reducing agents. Acids.

Hazardous Decomposition Products: May include, and are not limited to: oxides of carbon, oxides of nitrogen.

Possibility of Hazardous Reactions: No dangerous reaction known under conditions of normal use.

Section 11: TOXICOLOGY INFORMATION

EFFECTS OF ACUTE EXPOSURE

Component Analysis

Ingredient	LD₅₀ (oral)	LC₅₀
Ethanol	7060 mg/kg, rat	20000 ppm 10hr, rat
Isobutane	Not available.	658 mg/L 4hr, rat
Propane	Not available.	658 mg/L 4hr, rat
Triethylene glycol	Not available.	Not available.
Isopropanol	4396 mg/kg, rat	72.6 mg/L 4hr, rat

Eye: May cause eye irritation. Symptoms may include discomfort or pain, excess blinking and tear production, with possible redness and swelling.

Skin: May cause skin irritation. Symptoms may include redness, drying, and cracking of the skin.

Ingestion: Not a normal route of exposure. Harmful: may cause lung damage if swallowed.

Inhalation: May cause respiratory tract irritation. This product may be aspirated into the lungs and cause chemical pneumonitis. Vapours may cause drowsiness and dizziness.

EFFECTS OF CHRONIC EXPOSURE

Target Organs: Not available.

Chronic Effects: (Effects due to excessive exposure to the raw materials of this mixture)
Intentional excessive overexposure may cause kidney damage, liver abnormalities, brain damage.

Carcinogenicity: Not hazardous by OSHA criteria.

MATERIAL SAFETY DATA SHEET

Oster Kool-Lube 3

Ingredient

Chemical Listed as Carcinogen or Potential Carcinogen *

Ethanol	G-A3, I-1
Isobutane	Not listed.
Propane	Not listed.
Triethylene glycol	Not listed.
Isopropanol	G-A4, I-3

* See Section 15 for more information.

Mutagenicity: Hazardous by OSHA criteria.

Reproductive Effects: Not hazardous by OSHA criteria.

Developmental Effects:

Teratogenicity: Not hazardous by OSHA criteria.

Embryotoxicity: Not hazardous by OSHA criteria.

Respiratory Sensitization: Not hazardous by OSHA criteria.

Skin Sensitization: Not hazardous by OSHA criteria.

Toxicologically Synergistic Materials: Not available.

Section 12: ECOLOGICAL INFORMATION

Ecotoxicity: May cause long-term adverse effects in the aquatic environment.

Persistence / Degradability: Not available.

Bioaccumulation / Accumulation: Not available.

Mobility in Environment: Not available.

Section 13: DISPOSAL CONSIDERATIONS

Disposal Instructions:

This material must be disposed of in accordance with all local, state, provincial, and federal regulations.

Section 14: TRANSPORTATION INFORMATION

DOT Classification

ORM-D

Section 15: REGULATORY INFORMATION

Federal Regulations

US: MSDS prepared pursuant to the Hazard Communication Standard (29 CFR 1910.1200).

SARA Title III

Ingredient	Section 302 (EHS) TPQ (lbs.)	Section 304 EHS RQ (lbs.)	CERCLA RQ (lbs.)	Section 313
Ethanol	Not listed.	Not listed.	Not listed.	Not listed.
Isobutane	Not listed.	Not listed.	Not listed.	Not listed.
Propane	Not listed.	Not listed.	Not listed.	Not listed.
Triethylene glycol	Not listed.	Not listed.	Not listed.	Not listed.
Isopropanol	Not listed.	Not listed.	Not listed.	Yes.

MATERIAL SAFETY DATA SHEET

Oster Kool-Lube 3

State Regulations

California Proposition 65:

This product does not contain a chemical known to the State of California to cause cancer, birth defects or other reproductive harm.

Global Inventories

Ingredient

Ethanol
Isobutane
Propane
Triethylene glycol
Isopropanol

**USA
TSCA**
Yes.
Yes.
Yes.
Yes.
Yes.

HMIS - Hazardous Materials Identification System

Health - 2*

Flammability - 2

Physical Hazard - 0

PPE – B

NFPA - National Fire Protection Association:

Health - 2

Fire - 2

Reactivity - 0

Hazard Rating: 0 = minimal, 1 = slight, 2 = moderate, 3 = severe, 4 = extreme

SOURCE AGENCY CARCINOGEN CLASSIFICATIONS:

OSHA (O) Occupational Safety and Health Administration.

ACGIH (G) American Conference of Governmental Industrial Hygienists.

A1 - Confirmed human carcinogen.
A2 - Suspected human carcinogen.
A3 - Animal carcinogen.
A4 - Not classifiable as a human carcinogen.
A5 - Not suspected as a human carcinogen.

IARC (I) International Agency for Research on Cancer.

1 - The agent (mixture) is carcinogenic to humans.
2A - The agent (mixture) is probably carcinogenic to humans; there is limited evidence of carcinogenicity in humans and sufficient evidence of carcinogenicity in experimental animals.
2B - The agent (mixture) is possibly carcinogenic to humans; there is limited evidence of carcinogenicity in humans in the absence of sufficient evidence of carcinogenicity in experimental animals.
3 - The agent (mixture, exposure circumstance) is not classifiable as to its carcinogenicity to humans.
4 - The agent (mixture, exposure circumstance) is probably not carcinogenic to humans.

NTP (N) National Toxicology Program.

1 - Known to be carcinogens.
2 - Reasonably anticipated to be carcinogens.

Section 16: OTHER INFORMATION

Disclaimer:

We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. It is the user's responsibility to satisfy oneself as to the suitability and completeness of this information for the user's own particular use.

Prepared by: Nexreg Compliance Inc.

Prepared for: Oster Professional Products / Sunbeam Product Inc., D/B/A Jarden Consumer Solutions

Oster Customer Service (800) 339-2547 (CST) 8 AM- 5 PM

Safety Questions: (888)-865-6810 (CST) 7 AM-5:30 PM