

Safety Data Sheet

Big Sexy Hair Volumizing Dry Shampoo

SECTION 1: IDENTIFICATION

MSDS FIRST PREPARATION DATE: January 30, 2015 FORMULA: B-9312 GENERIC/CHEMICAL NAME: Aerosol PRODUCT TYPE/CHEMICAL FAMILY: Personal Care Product PRODUCT CODE: N/A SYNONYMS: None CONTACT ADDRESS: Sexy Hair Concepts, LLC 21551 Prairie St. Chatsworth, CA 91311

EMERGENCY PHONE NUMBERS: Chem-tel: (800) 255-3924 – 24-Hours ; Contract number: MIS0002907

SECTION 2: HAZARDS IDENTIFICATION

This product is classified as a HAZARDOUS SUBSTANCE and as DANGEROUS GOODS according to the classification criteria of NOHSC: 1008 (2004) and ADG Code (Australia).

WARNING! EXTREMELY FLAMMABLE AEROSOL. PRESSURIZED CONTAINERS : MAY BURST IF HEATED. CAUSES EYE IRRITATION.

Classification: Aerosols 3

Hazard statements (H):

H222	Extremely Flammable Aerosol
H229	Pressurized container: may burst if heated
H320	Causes eye irritation

Precautionary statements (P):

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211	Do not spray on an open flame or other ignition source.
P251	Do not pierce or burn, even after use.
P261	Avoid breathing vapor/spray.
P264	Wash thoroughly with soap and water after handling.
P271	Use only in a well-ventilated area.
P280	Wear eye protection.
P304+340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove Contact lenses if present and easy to do so. Continue rinsing.
P337+P313	If eye irritation persists: Get medical advice/attention
P410 + P412	Protect from sun light. Do not expose to temperature exceeding 50 °C/122 °F.
P501	Dispose of contents/containers to licensed and permitted disposal or recycling facility.

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

Composition:

		Exposure Limits in Air (mg/m³)											
					ACO	ЭIH		NOHSC			OSHA		
					рр	m		ppm	1		ppm	r	
Chemical Name (s)	CAS No.	RTECS No.	EINECS No.	%	TLV	STEL	ES- TWA	ES- STEL	ES- PEAK	PEL	STEL	IDLH	Other
Isobutane	75-28-5	TZ4300000	200-857-2	10-30	600	750	NF	NF	NF	NA	NA	NA	
	Flam.Gas 1; G	Flam.Gas 1; Gas; H220											
Ethanol (SD Alcohol	64-17-5	KL 4100000	200-866-1	15-40	1000	3000	1000	1800	NF	1000	1900	3300	
40-B)	Flam. Lig. 2; I	H225											
Butane	74-98-6	TX2275000	203-448-7	10-30	600	NA	NF	NA	NA	NE	NA	NA	
Butane	Press. Gas 1;	Flam. Gas 1; H220	•										
Propane	74-98-6	TX2275000	200-827-9	10-30	1000	NA	1000	NF	NF	100	NA	2100	
· · opuno	Press. Gas 1;	Flam. Gas 1; H220											

SECTION 4: FIRST AID MEASURES

4.1 First Aid:

- **Ingestion:** If ingested do not induce vomiting! If product has been swallowed drink plenty of water or milk IMMEDIATELY. If the patient is vomiting, continue to offer water or milk. Never give water or milk to an unconscious person. Contact the nearest Poison Control Center or local emergency number. Provide an estimate of the time at which the material was ingested and the amount of substance that was swallowed.
- **Skin:** If irritation occurs & product is on the skin, rinse thoroughly with lukewarm water, followed by a thorough washing of the affected area with plenty of soap and water. Remove contaminated clothing and wash thoroughly before reuse. If irritation, redness or swelling persists, consult a physician immediately.
- **Eyes:** If product gets in the eyes, flush with copious amounts of lukewarm water for at least 15 minutes. Raise and lower eyelid(s) while flushing to ensure thorough irrigation. If problem persist seek immediate medical attention.
- **Inhalation:** In the event of massive inhalation Remove Victim to fresh air and keep comfortable for breathing.

4.2 Effects of Exposure:

- **Ingestion:** If product is swallowed, may cause vomiting and/or diarrhea and central nervous system depression.
- **Eyes:** Moderately irritating to the eyes.
- Skin: May be irritating to skin. The product can cause allergic skin reactions (e.g., rashes, welts, dermatitis) in some sensitive individuals upon prolonged or repeated exposure.
- Inhalation: Vapors of this product may be moderately irritating to the nose, throat and other tissues of the respiratory system. Symptoms of overexposure can include coughing, wheezing, nasal congestion, and difficulty breathing. Inhalation of

concentrated vapors can cause central nervous system depression (e.g., drowsiness, dizziness, headaches, nausea).

4.3 Symptoms of Overexposure:

- **Ingestion:** May cause vomiting and/or diarrhea and central nervous system depression.
- Eyes: Overexposure in eyes may cause redness; itching and watering (risk of serious damage to eyes). Contact may cause mild eye irritation including stinging, watering and redness.
- **Skin:** Prolonged contact with skin may result in bleaching and irritation of skin. The product can cause allergic skin reactions (e.g., rashes, welts, dermatitis) in some sensitive individuals. Symptoms of skin overexposure may include redness, Itching, and irritation of affected areas.
- **Inhalation:** Symptoms of overexposure may include coughing, wheezing, nasal congestion, and difficulty breathing.

4.4 Acute Health Effects:

Moderate irritation to eyes and skin near affected areas. Additionally, high concentrations of vapors can cause drowsiness, dizziness, headaches and nausea.

4.5 Chronic Health Effects:

No harmful or chronic health effects are expected to occur from a single accidental ingestion. These ingredients may be irritating to the skin and mucous membrane of the eye and respiratory system. Overexposure may trigger asthma-like symptoms in some sensitive individuals. May also induce skin sensitization and respiratory hypersensitivity. Possible allergic dermatitis.

4.6 Target Organs:

Eyes, skin, respiratory system.

4.7 Medical Conditions Aggravated by Exposure:

Acute health hazards may be delayed. Most common symptoms include irritating properties to eyes, respiratory system and skin. Existing dermatological conditions (such as eczema) and respiratory conditions (such as bronchial asthma and/or bronchitis) may be exacerbated.

HEALTH	1	2
FLAMM	3	
PHYSIC	0	
PROTE	В	
EYES	SKIN	

SECTION 5: FIRE FIGHTING MEASURES

5.1 Fire & Explosion hazards:

Level 3 Aerosol (NFPA 30B), Aerosols may burst at temperatures above 120 °F. Cool uninvolved containers to prevent possible bursting. Aerosols may be projectile hazards when bursting. If aerosols are bursting, stay clear until bursting is complete. Containers may rupture and release flammable liquids or exposed gasses if exposed to the heat of fire. Keep containers cool by spraying them with water until the fire has been extinguished.

5.2 Extinguishing Methods:

Water Fog, Foam, Dry Chemical, CO₂



Page **3** of **10**

5.3 Firefighting Procedures

As in any fire, wear MSHA/NIOSH approved self-contained breathing apparatus (pressure demand) full and protective gear. Keep containers cool until well after the fire is out. Use water spray to cool fire exposed surfaces and to protect personnel. Fight fire upwind. Avoid spraying water directly into storage containers because of danger of boil over. Prevent run off from fire control or dilution from entering sewers, drains, drinking water supply, or any natural waterway. Firefighters must use full bunker gear including NIOSH- approved positive pressure self-contained breathing apparatus to protect against potential hazardous combustion or decomposition products and oxygen deficiencies.

SECTION 6: ACCIDENTIAL RELEASE MEASURES

- **Spills:** Before cleaning any spill or leak, individual involved in a spill cleanup must wear appropriate Personal Protective Equipment. Plastic or rubber gloves, respirator, eye protection and apron may be required for clean-up of large spills.
- **Small Spills:** Wear appropriate protective equipment including gloves and protective eyewear. Use a non-combustible material such as vermiculite or sand to soak up the product and place into a container for later disposal. Do not use water or a material such as "speed dry" to soak up material. Sweep up material using non-sparkling materials (e.g., plastic brooms, shovels, dustpans) and place into a plastic container or plastic liner within another container.
- Large Spills: Keep incompatible materials (e.g., organics such as oil) away from spill. Stay upwind and away from spill or release. Isolate immediate hazard area and keep unauthorized personnel out of area. Stop spill or release if it can be done with minimal risk. Wear appropriate protective equipment including respiratory protection as conditions warrant.

SECTION 7: HANDLING AND STORAGE

7.1 Work & Hygiene Practices:

Do not eat, drink or smoke when handling this product. Contents under pressure. Handle as to avoid puncturing container(s). When used as intended, no additional protective equipment is necessary. Use chemical goggles if eye contact is possible. Wash unintentional residues with soap and warm water.

7.2 Storage & Handling:

Use and store in a cool, dry, well-ventilated location (e.g., exhaust ventilation fans) away from heat and direct sunlight. Avoid temperatures above 120°F. Keep away from incompatible substances. Protect containers from physical damage. To avoid unintentional spraying keep cap in place when not in use. Storage level 1

7.3 Special Precautions:

Spilled material presents a slipping hazard if left unattended. Clean all spills promptly.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 Exposure Limits ppm (mg/m³)

	AC	GIH		NOHSC			OSHA		
Chemical Name(s)	TLV	STEL	ES-TWA	ES-STEL	ES-PEAK	PEL	STEL	IDLH	other
Isobutane	600	750	NF	NF	NA	NA	NA	NA	
Butane	1000	NA	1000	NF	NF	800	NA	NA	
Propane	1000	NA	1000	NF	NF	1000	NA	2100	

8.2 Ventilation & Engineering Controls:

General mechanical (e.g., fans) or natural ventilation is sufficient when this product is in use. Use local or general exhaust ventilation to effectively remove and prevent buildup of vapors or mist generated from the handling of this product.

8.3 Respiratory Protection:

No special respiratory protection is required under typical circumstances of use or handling. In instances where dusts of this product are generated, and respiratory protection is needed, use only protection authorized by 29 CFR 1910.134, applicable U.S State regulations, or the Canadian CAS standard Z94.4-93 and applicable standards of Canadian Provinces, EC member states, or Australia.

8.4 Eye Protection:

Avoid eye contact. None required under normal conditions of use. Safety glasses could be used when handling or using large quantities of this product.

8.5 Hand Protection:

None required under normal conditions of use. However may cause skin irritation in some sensitive individuals. When handling large quantities (e.g., \geq 1 gallon (3.8L)), wear rubber, nitrite or impervious plastic gloves.

8.6 Body Protection:

No apron needed when handling small quantities. When handling large quantities (e.g., \geq 5 lbs), eye wash stations and deluge showers should be available. Upon completion of work activities involving large quantities of this product, wash any exposed areas thoroughly with soap and water.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1 Appearance:	Aerosol
9.2 Odor:	Floral Odor
9.3 Odor Threshold:	NA
9.4 pH:	NA
9.5 Melting Point / Freezing Point:	NA
9.6 Initial Boiling Point/Boiling Point:	NA
9.7 Flash Point (°C):	-30 °F (-34 °C) TCC for propellant only 36 °F (2.2 °C) EPA method concentrate only
9.8 Upper/lower Flammability Limits:	UEL 9.5% V; LEL 1.8% V
9.9 Vapor Pressure:	@ 20 °C (68 °F) - Can pressure not to exceed 180 psig @ 55 °C (131 °F) 12.4 bar
9.10 Vapor Density:	> 1
9.11 Relative Density:	0.81 – 0.85
9.12 Solubility:	Insoluble
9.13 Partition Coefficient (log PG ow):	NA
9.14 Autoignition Temperature:	NA
9.15 Decomposition Temperature: 9.16 Viscosity:	NA NA
9.17 Other Information:	Evaporation rate > 1: Percent Volatile 94%

SECTION 10: STABILITY AND REACTIVITY

10.1 Stability: Stable at normal temperatur	es.					
10.2 Hazardous Decomposition Pro Oxides of carbon (CO, CO ₂)						
10.3 Hazardous Polymerization: Will not occur						
10.4 Conditions to avoid Excessive heat, direct sunlight	nt, flames, heat sources a	nd incompatible substances				
10.5 Incompatible substances: Mixture with strong acids, alk	alis or oxidizers					
SECTION 11: TOXICOLOGICAL	INFORMATION					
11.1 Routes of Entry:						
Inhalation : YES	Absorption: YES	Ingestion: YES				
11.2 Toxicity data:	in scientific literature is	tested on animals. Toxicology data, found s available for some of the components of sented below: <u>Propane: LD50 (Inhalation,</u>				
11.3 Acute Toxicity:	See section 4.4					
11.4 Chronic Toxicity:	See section 4.5					
11.5 Suspected Carcinogen:	No					
11.6 Reproductive Toxicity:	This product is no reported to cause reproductive toxicity in humans.					
Mutagenicity:	This product is no repo humans.	orted to produce mutagenic effects in				
Embryotoxicity:		orted to produce embryotoxic effects in				

humans

humans.

NE

See section 4.3

Treat symptomatically

SECTION 12: ECOLOGICAL INFORMATION

12.1 Environmental Stability:

Teratogenicity:

11.7 Irritancy of Product:

Reproductive Toxicity:

11.8 Biological Exposures indices:

11.9 Physician Recommendations:

There is no specific data available for this product.

12.2 Effects on Plants & Animals:

There is no specific data available for this product.

12.3 Effects on Aquatic Life:

This product itself has not been tested as a whole. There is no specific data available for this product.

This product is no reported to cause teratogenic effects in

This product is no reported to cause reproductive effects in

SECTION 13: DISPOSAL CONSIDERATIONS

13.1 Waste Disposal:

Review current local, state and federal laws, codes, statutes and regulations to determine current status and appropriate disposal method for the ingredient listed in Section 2. Any disposal practice must be in compliance with local, state, and federal laws and regulations. Contact the appropriate agency for specific information. A licensed facility or waste hauler must provide treatment, transport, storage and disposal of hazardous waste.

13.2 Special Considerations: U.S. EPA Hazardous waste - Characteristic- Ignitable (D001)

SECTION 14: TRANSPORT INFORMATION

The basic description (ID number, proper shipping name, hazard class & division, packing group) is shown for each mode of transportation. Additional descriptive information may be required by 49 CFR, IATA/ICAO, IMDG and the CTDGR.

14.1 49 CFR (GND):	UN 1950, AEROSOLS, 2.1 (LTD QTY, IP VOL ≤ 1.0 L); or CONSUMER COMMODITY, ORM-D (IP VOL ≤ 1.0 L) - until 12/31/2020	
14.2 IATA (AIR)	UN 1950, AEROSOLS, FLAMMABLE, 2.1 (LTD QTY, IP VOL \leq 0.5 L); or ID8000, CONSUMER COMMODITY, ORM-D (IP VOL \leq 0.5 L)	$\mathbf{\mathbf{X}}$
14.3 IMDG (OCN):	UN 1950, AEROSOLS, 2.1 (LTD QTY, IP VOL ≤ 1.0 L)	1.4499445.5 EAS
14.4 TDGR (CANADIAN	GND) UN 1950, AEROSOLS, 2.1 (LTD QTY, IP VOL ≤ 1.0 L); or MARK PACKAGE "LIMITED QUANTITY," "LTD QTY," or "QUANT LTÉE" or "QUANTITE LIMITÉE"	<u>ر</u>
14.5 ADR/RID (EU):	UN 1950, AEROSOLS, 2.1 (LTD QTY, IP VOL \leq 1.0 L)	2/11
14.6 SCT (MEXICO):	UN 1950, AEROSOLS, 2.1 (CANTIDAD LIMITADA, IP VOL \leq 1.0 L)	$\langle \mathbf{n} \rangle$
14.7 ADGR (AUS):	UN 1950, AEROSOLS, 2.1 (LTD QTY, IP VOL ≤ 1.0 L)	\searrow

SECTION 15: REGULATORY INFORMATION

15.1 SARA Reporting Requirements:	This product does not contain any substances subject to SARA Title III, Section 313 reporting requirements.
15.2 SARA Threshold Planning Quan	tity: There are no specific Threshold Planning Quantities for the components of this product.
15.3 TSCA Inventory Status:	The components of this product are listed in the TSCA Inventory.
15.4 CERCLA Reportable Quantity (R	Q): Ethanol: 2,279 kg (5,000 lbs)
15.5 Other Federal Requirements:	This product complies with the appropriate sections of the Food and Drug Administration's 21 CFR Subchapter G, (Cosmetics)
15.6 Other Canadian Regulations:	This product has been classified according to the hazard criteria of the CPR and MSDS contains all of the information required by the CPR. The components of this product are listed on the DSL/NDSL. None of the components of this product are listed on the Priorities Substances List. WHMIS Class B5 (Flammable Aerosol).



15.7 State Regulatory Information:

(MA), Pennsylvania Right-to-know List (PA), New Jersey Right-to-know List (NJ),

Propane and Butane can be found on the following State criteria lists: MA, MN, NJ PA AND WA

No other ingredients in this product, present in concentration of 1.0% or greater are listed on any of the following state criteria lists: California Proposition 65 (CA65), Delaware Air Quality Management List (DE), Florida Toxic Substances List (FL), Massachusetts Hazardous Substances List (MA), Michigan Critical Substances List (MI), Minnesota Hazardous Substances Lists (MN) New Jersey Right-to-know List (NJ), New York Hazardous Substances List (NY), Pennsylvania Right-to-know List (PA), and Washington Permissible Exposures List (WA), Wisconsin Hazardous Substances List (WI).

15.8 Other Requirements:

The primary components of this product are listed in Annex I of EU Directive 67/548/EEC.

Isobutane : Flammable (F+). <u>Risk Phrases</u> (R):12- Highly Flammable, <u>Safety Phrases</u> (S): 2-9-16-- Keep out of reach of children. Keep container in a well-Ventilated place. Keep away from sources of ignition – No Smoking.



Propane: Flammable (F+). Risk Phrases (R):12- Highly Flammable, Safety Phrases (S): 2-9-16--Keep out of reach of children. Keep container in a well-Ventilated place. Keep away from sources of ignition – No Smoking.

Butane: Butane: Flammable (F+). Risk Phrases (R): 12 - Extremely flammable. Safety Phrases (S): 2-6-16

-53-46 - Keep out of reach of children. Keep cool store below 120 0F (48.8 0C). Keep away from sources of ignition - No smoking. Avoid exposure - obtain special instruction before use. In case of

an accident or if you fell unwell seek medical advice immediately.

<u>Ethanol</u>: Flammable (F+). <u>Risk Phrases</u> (R):11- Flammable, <u>Safety Phrases</u> (S): 2-7-16-- Keep out of reach of children. Keep container tightly closed Keep away from sources of ignition – No Smoking.

SECTION 16: OTHER INFORMATION

16.1 Other Information:

WARNING! FLAMMABLE AEROSOL. PRESSURIZED CONTAINER: MAY BURST IF HEATED. HIGHLY FLAMMABLE LIQUID AND VAPOR. CAUSES EYE IRRITATION.

Keep away from heat, sparks, open flames and/or other ignition sources. No Smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Avoid breathing vapor/spray. Wash thoroughly with soap and water after handling. Use only in a well-ventilated area. Wear eye protection. Protect from sunlight. Do not expose to temperatures exceeding 50 °C (122 °F). IF INHALED: remove person to fresh air and keep comfortable for breathing. IF IN EYES: Rinse cautiously with water for several minutes remove contact lenses if present and easy to do. Continue rinsing. If eye irritation persists: get medical advice/attention. **KEEP LOCKED UP AND OUT OF REACH OF CHILDREN.**

16.2 Terms & Definitions: See last page of this Safety Data Sheet.

16.3 Disclaimer:


This Safety Data sheet is offered pursuant to OSHA's Hazard Communication Standard 29 CFR 1910.1200. Other government regulations must be reviewed for applicability to this product. To the best of Sexy Hair Concepts, LLC knowledge, the information contained herein is reliable and

accurate as of this date; however accuracy, suitability or completeness are not guaranteed and no warranties of any type, either expressed or implied, are provided. The information contained herein relates only to the specific product(s). If this product(s) is combined with other materials, all component properties must be considered. Data may be changed from time to time. Be sure to consult the latest edition.

	RAL IN			Service Nu	mber					
	SURE L	and the second		Dervice IV	inder					
	ACGIH		American Conference on Governmental Industrial Hygienists							
	С	Ceiling L	₋imit							
				d (Australia erous to Lif		lth				
	OSHA			Safety and			on			
	PEL		ible Expos							
	STEL TLV		erm Expos							
	TWA		eighted Av							
RST	AID ME	ASUR	ES:							
	CPR	stopped	receives	resuscitatio manual che en to the boo	st compre					
MIS	III HEAL		and the second	BILITY & F	Second and the second	ITY RAT	INGS:			
0	Minimal	Hazard			HE	ALTH				
1	Slight H	azard					BILIT	(
2	-	te Hazard	d		A REAL PROPERTY OF		L HAZ		;	
3	Severe	220 227					AL PR			
4		Hazard						UTLO		
				ATINGS:						
1	6				G	0				
3	0				н	0			8	
:	0				I	0				
>	B				J	0		Î		
	0		\bigcirc		к					
=	0			0	x		your sup handling			
Safe	ety Glass	es	Splash	Goggles		e Shield &		Glove) S	
	Boots		Synthet	ic Apron		tive Cloth	ing I	Qust Res	Dirator	
ull Fa	(P) Ice Respi	rator		apor Half-	F	Full Suit	Ai	rline Hoo		
				spirator		spirator		or SCI	BA	
HE	ML		um Limit	VIATIONS						
	mg/m3			ubic meter						
	NA	Not Av	ailable							
	ND NE		atermined tablished							
	NE	Not Es								
	NR	No Re	sults							
	ppm		er million	and the state						
	SCBA			Breathing Ap		NER				
				ON ASSO	CIATION	: NFPA				
LAN	MABILI		ITS IN A	2012.0						
	oignition			rature requ	ired to in	tiate com	bustion in	air with	no other	
1 em	perature LEL		of ignition		est perce	nt of vap	orin air b	v volume	that will	
			Lower Explosive Limit - lowest percent of vapor in air, by volume, that will explode or ignite in the presence of an ignition source							
	UEL	explod		in the pres Limit - hig						

ARD RATINGS:

0	Minimal Haz	ard					
1	Slight Hazard						
2	Moderate Ha	azard					
3	Severe Haza	ard					
4	Extreme Ha	zard					
ACD	Acidic						
ALK	Alkaline						
COR	Corrosive						
₩	Use No Water						
OX	Oxidizer						
TREFOIL	Radioactive						
TOXICOLO	GICAL INFO	ORMATION:					
	LD ₅₀	Lethal Dose (solids & liquid					
	LC ₅₀	Lethal concentration (gases					



	LD ₅₀	Lethal Dose (solids & liquids) w	PRECAUTIONS				
	LC ₅₀	Lethal concentration (gases) which kills 50%	of the exposed animal				
	ppm	Concentration expressed in parts of material	per million parts				
	TD _{lo}	Lowest dose to cause a symptom					
	TCLo	Lowest concentration to cause a symptom					
	Dio, & LDo or	Lowest dose (or concentration) to cause leth	al or toxic effects				
TC, TC _o ,	LC _{Io} , & LC _o	0.000 98					
	IARC	International Agency for Research on Cance	r				
	NTP	National Toxicology Program					
	RTECS	Registry of Toxic Effects of Chemical Substances					
	BCF	Bioconcentration Factor					
1	TLm	Median threshold limit					
log Kov	w or log Koc	Coefficient of Oil/Water Distribution					
REGULATO	ORY INFOR	MATION:					
WHMIS	Canadian Workplace Hazardous Material Information System						
DOT	T U.S. Department of Transportation						
TC	Transport C	anada					
EPA	U.S. Environmental Protection Agency						

EPA	U.S. Environmental Protection Agency
DSL	Canadian Domestic Substance List
NOHSC	National Occupational Health and Safety Commission (Australia)
NDSL	Canadian Non-Domestic Substance List
PSL	Canadian Priority Substances List
TSCA	U.S. Toxic Substance Control Act
EU	European Union (European Union Directive 67/548/EEC)
WGK	Wassergefährdungsklassen (German Water Hazard Class)
HMIS-III	National Paint & Coatings Association Hazardous Materials Identification System
	· · · · · · · · · · · · · · · · · · ·

		-	-				
Class A	Class B	Class C	Class D1	Class D2	Class D3	Class E	Class F
Compressed	Flammable	Oxidizing	Toxic	Irritation	Infectious	Corrosive	Reactive

		N.	¥2	8	2	X	×
с	E	F	N	0	т	Xi	Xn
Corrosive	Corrosive Explosive		Harmful	Oxidizing	Toxic	Irritant	Harmful

GHS (1272/2008/EC) PICTOGRAMS:

		٨	\Diamond					
GHS01	GHS02	GHS03	GHS04	GHS05	GHS06	GHS07	GHS08	GHS09
Explosive	Flammable	Oxidizer	Pressurized	Corrosive	Toxic	Harmful Irritating	Health Hazard	Environment